

Terxon LX LCD Keypad

Art.-Nr. AZ4210

Seite 1 von 2



The Terxon LX LCD Keypad is an extension module for the Terxon LX. Installed near the entrance door, it allows you to quickly operate your alarm control panel. The LCD keypad is connected to the Terxon LX via a 5-wire bus cable. Up to 128 control units can be integrated into the alarm system. Arranged in various parts of your building, these extension modules provide additional convenience. The system can be conveniently activated or deactivated via any keypad using a PIN code and proximity chip key. The status of the alarm control panel is also displayed on the plain text display of the control unit. You can conveniently view and, of course, change system settings, programming and the 2000x event memory of the Terxon LX. The LCD keypad is designed in an elegant white color. Thus, it is not only an enhancement for each entrance area, but it is also optically in line with the wireless components of the Secvest 2WAY. Whenever you extend your alarm system, for example, with a wireless universal module or an 8-zone wireless extension, all wireless extension components of the Secvest 2WAY will match your existing system perfectly, not only from a technical standpoint, but also visually.

Technologies

- For operating and programming the alarm panel
- Suitable for indoor and protected outdoor use
- Operate your alarm panel with PIN code or proximity key fob
- Proximity chip reader integrated

Technical data - Terxon LX LCD Keypad

Colour	white
Connections	5-core bus, screw terminal for connection of two zones, loudspeaker
Current consumption	30 mA
DC power supply	12 V
Depth	23 mm
Dimensions	(WxHxD) 134x134x23 mm

Terxon LX LCD Keypad

Art.-Nr. AZ4210

Seite 2 von 2

Technical data - Terxon LX LCD Keypad

Display type	Alphanumeric LCD display, 2 lines x 16 segments
Environmental class	II
Height	134 mm
Housing material	ABS
Integrated siren	Yes
Length	23 mm
Max. Air humidity	94 %
Max. Operating temperature	55 °C
Mechanical protection	No
Min. operating temperature	-10 °C
Mounting location	Indoors and protected outdoor areas
Net weight	0.3 kg
Number of rooms / groups	1
Outputs	1 transistor switch output
PSTI conformity needed	No
Power consumption	0.36 W
Product group	Operation
Protection class IP	54
Security gradient	2
Switching outputs	1
Tamper monitoring	Yes
Touchpanel	No
VdS class	without
WEEE group	09
Zone closure	2 DEOL (FSL) if connected to bus (alarm panel)
width	134 mm