

Terxon LX 8-Zone Wired Extension with PSU

Art.-Nr. AZ4250

Seite 1 von 2



Technical data - Terxon LX 8-Zone Wired Extension with PSU

AC power supply	230 V
Battery type	7 Ah or 17 Ah, 12 V DC rechargeable battery
Connections	5-wire bus
Current consumption	145 mA
Dimensions	(WxHxD) 382x310x95 mm
Emergency power supply	Yes
Height	310 mm
Housing material	Metal
Integrated siren	No
Length	95 mm
Max. Air humidity	96 %
Max. Operating temperature	55 °C
Mechanical protection	No
Min. operating temperature	-10 °C
Mounting type	Surface mounted
Net weight	4.415 kg
Number of wire zones	8
Outputs	1, positive switching 500mA
PSTI conformity needed	No
Security level	4 fuses (500 mA), automatically resettable; 1 main fuse (T315 mA / 250 V)
Switching outputs	1
Tamper lines	8
Tamper monitoring	Yes
VdS class	without

Terxon LX 8-Zone Wired Extension with PSU



Security Tech Germany

Art.-Nr. AZ4250

Seite 2 von 2

Technical data - Terxon LX 8-Zone Wired Extension with PSU

Voltage monitoring	Yes
WEEE group	09
Zone closure	NC, DEOL (FSL)
width	382 mm