

VdS Surface Mount Panic Alarm Button

Art.-Nr. AZ6500

Seite 1 von 2



If you press the panic button, you trigger a silent alarm to call for help. You can use the panic button as a standalone device or integrate it into the burglar alarm system. The button is tamper-monitored. For panic and tamper alarms, you have an NO or NC contact. The panic button is VSÖ and VdS C certified.

Technologies

- Simple surface mounting
- Inconspicuous, discreet alarm signalling
- Certified VdS Class C

Technical data - VdS Surface Mount Panic Alarm Button

Certifications	VdS-C
Colour	white
Compatible with	Secoris, Secvest, Terxon
Connections	1 x NO/NC alarm contact; 1x NO/NC tamper contact
Depth	47 mm
Diameter	85 mm
Dimensions	(WxHxD) 85x85x47 mm
Height	85 mm
Housing material	ABS
Length	47 mm
Max. Operating temperature	55 °C
Mechanical protection	No
Mounting location	Surface or flush fitting
Net weight	0.166 kg
Number of rooms / groups	1

VdS Surface Mount Panic Alarm Button

Art.-Nr. AZ6500

Seite 2 von 2

Technical data - VdS Surface Mount Panic Alarm Button

PSTI conformity needed	No
Product group	Detectors
Protection class IP	32
Switching outputs	Maximum switching power: 3 A/75 V
Switching power	225 W
Tamper monitoring	Yes
Touchpanel	No
Type of protection	Intrusion protection
VdS approval no.	G 192028
VdS class	C
VdS recognized	Yes
WEEE group	09
width	85 mm