

# 10 m Preassembled Video Combination Cable

Art.-Nr. TVAC40110

Seite 1 von 2



Save time during installation!

This pre-assembled video combination cable is an extremely practical accessory for analogue video surveillance cameras. It can be used both for video signal transmission and power supply. Not only are the video signal and power supply combined in one cable, but the cable is also pre-assembled ready for connection, saving you the time-consuming tasks of stripping wires, clamping and crimping. The pre-assembled video combination cable is available in lengths of 10 m (TVAC40110), 20 m (TVAC40120) and 30 m (TVAC40130).

Note: Pre-assembled video cables TVAC40110, TVAC40120 and TVAC40130 are only compatible with the analogue HD cameras HDCC31500 and HDCC41500.

## Technologies

- Video signal and power supply combined in one cable
- Pre-assembled BNC and DC connections
- Suitable for all analogue cameras with BNC socket (female) and power supply connection (male)
- Available in different lengths

## Technical data - 10 m Preassembled Video Combination Cable

|                            |                           |
|----------------------------|---------------------------|
| Application purpose        | indoors                   |
| Attenuation                | 0.53 dB                   |
| Cable length               | 10 m                      |
| Cable style                | Combined video cable      |
| Colour                     | black                     |
| Connection type            | BNC (male) - BNC (female) |
| DC power supply            | 12 V                      |
| Diameter                   | 6 mm                      |
| Housing material           | PVC                       |
| Impedance                  | 75 Ω                      |
| Insulation                 | PE                        |
| Max. operating temperature | 60 °C                     |

# 10 m Preassembled Video Combination Cable

Art.-Nr. TVAC40110

Seite 2 von 2

## Technical data - 10 m Preassembled Video Combination Cable

|                            |             |
|----------------------------|-------------|
| Min. operating temperature | -10 °C      |
| Net weight                 | 0.298 kg    |
| Outside diameter           | 6 mm        |
| PSTI conformity needed     | No          |
| Product group              | Accessories |