

20 m Preassembled Video Combination Cable

Art.-Nr. TVAC40120

Seite 1 von 2



Save time during installation!

This pre-assembled video combination cable is an extremely practical accessory for analogue video surveillance cameras. It can be used both for video signal transmission and power supply. Not only are the video signal and power supply combined in one cable, but the cable is also pre-assembled ready for connection, saving you the time-consuming tasks of stripping wires, clamping and crimping. The pre-assembled video combination cable is available in lengths of 10 m (TVAC40110), 20 m (TVAC40120) and 30 m (TVAC40130).

Note: Pre-assembled video cables TVAC40110, TVAC40120 and TVAC40130 are only compatible with the analogue HD cameras HDCC31500 and HDCC41500.

Technologies

- Video signal and power supply combined in one cable
- Pre-assembled BNC and DC connections
- Suitable for all analogue cameras with BNC socket (female) and power supply connection (male)
- Available in different lengths

Technical data - 20 m Preassembled Video Combination Cable

Application purpose	indoors
Attenuation	0.53 dB
Cable length	20 m
Cable style	Combined video cable
Colour	black
Connection type	BNC (male) – BNC (female)
DC power supply	12 V
Diameter	6 mm
Housing material	PVC
Impedance	75 Ω
Insulation	PE
Length	20000 mm

20 m Preassembled Video Combination Cable

Art.-Nr. TVAC40120

Seite 2 von 2

Technical data - 20 m Preassembled Video Combination Cable

Max. Operating temperature	60 °C
Min. operating temperature	-10 °C
Net weight	0.588 kg
Outside diameter	6 mm
PSTI conformity needed	No
Product group	Accessories