

Video Triplex Cable 250 m

Art.-Nr. TVAC40320

Seite 1 von 2



Triplex cable for the transmission of video and control data as well as power supply

Please note that this cable has not been tested and certified in accordance with the currently valid EU Construction Products Regulation.

This product is therefore not CPR-compliant. This means that it is not intended for permanent installation in structures.

Structures are houses or other buildings including tunnels, bridges, underground stations, etc. but not ships, buses, trains, etc.

Ensure the ideal connection of your PTZ dome cameras or Autofocus Zoom cameras with other components of your video surveillance system. The triplex cable offers an enormous practical advantage: Only a single cable is required for the transmission of the video image and control data (dome, zoom) as well as for power supply. In addition to the video cable (RG59), the cables for the control data (2 x 0.22 mm²) and the power cables (2 x 0.75 mm²) are already integrated. The triplex cable is suitable for outdoor use, the cable resistance is 75 ohms. The video triplex cable is available in lengths of 50 m (TVAC40300), 100 m (TVAC40310) and 250 m (TVAC40320).

Technologies

- Transmission of video image, power supply and control data
- Weather-resistant material
- UV-resistant cable
- Integrated RG59 coaxial cable, power cable 2 x 0.75 mm², control cable 2 x 0.22 mm²
- Length: 250 m

Video Triplex Cable 250 m

Art.-Nr. TVAC40320

Seite 2 von 2

Technical data - Video Triplex Cable 250 m

AC power supply	24 V
Application purpose	outdoors
Cable length	250 m
Cable style	Combined video cable
Cores	RG59 + 2x 0,75 mm ² + 2x 0,22 mm ²
Insulation	PVC
Max. Operating temperature	60 °C
Min. operating temperature	-15 °C
Net weight	24.045 kg
Outside diameter	102 mm
PSTI conformity needed	No
Product group	Accessories