

Secvest Wireless Window Handle FG 350 E (white)

Art.-Nr. FUFT50040W

Seite 1 von 2



Efficient locking without the risk of false alarms - only from ABUS

The Secvest wireless window handle uses magnetic field sensors to detect any unauthorised opening of the windows. If the window is opened while it is armed by the alarm system, a message is immediately sent to the Secvest wireless alarm system. The current status of the window (open or closed) is constantly transmitted wirelessly to the alarm panel, where the status display indicates that the window is open. The window is only considered closed by the system once it has been locked, ensuring reliable alarm triggering when a break-in occurs and minimising the risk of false alarms.

Quick and easy installation without drilling

The wireless window handle is installed very easily by replacing the existing handle, without having to drill in additional holes. The handle is available in white, brown and silver.

Technologies

- Greater security thanks to lock monitoring
- Reliably transmits the status of the window (open or closed) to the alarm panel
- Simple installation by replacing the existing window handle

Technical data - Secvest Wireless Window Handle FG 350 E (white)

Battery - max. battery life	3 years(s)
Battery - quantity	1
Battery type	1x lithium 1/2 AA, ER14250
Colour	white
Compatible with	Secvest, BUM060040
DC power supply	3,6 V
Detection method	Magnetic switch

Secvest Wireless Window Handle FG 350 E (white)

Art.-Nr. FUFT50040W

Seite 2 von 2

Technical data - Secvest Wireless Window Handle FG 350 E (white)

Dimensions	(WxHxD) 33x168x53 mm
Environmental class	II
Height	168 mm
Housing material	ABS, Stainless steel
Length	53 mm
Max. operating temperature	55 °C
Mechanical protection	No
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Windows and French windows
Net weight	0.4 kg
PSTI conformity needed	No
Product group	Detectors
Radio frequency	868.6625 MHz
Radio power	10 mW
Screw spacing	43 mm
Sensor type	Reed contact
Tamper monitoring	Yes
Technology	Mechatronics
Type of protection	Intrusion protection
VdS class	without
Voltage monitoring	Yes
width	33 mm