

Secvest Wireless Info Module

Art.-Nr. FUM050030

Seite 1 von 2



Acoustic and visual indication of system status

The Secvest wireless info module is an optional Secvest accessory. An LED display and various signal tones are used to indicate all processes and alarm system statuses. For example, input and output delays are indicated by a feedback tone via the info module. Faults, information on sub-areas, and zone statuses are also displayed on the info module. If an alarm is triggered, the internal piezo sounder also generates an internal alarm of about 90 dB.

Technologies

- Provides Secvest status information
- 8 LED displays
- Various signal and alarm tones
- Integrated piezo sounder

Technical data - Secvest Wireless Info Module

Battery type	none
Colour	white
Compatible with	Secvest, Terxon
Connections	12V
Current consumption	53 mA
DC power supply	9-14 V
Depth	40.7 mm
Dimensions	(WxHxD) 124x124x40.7 mm
Display type	8 LEDs of different colors
Environmental class	II
Height	124 mm
Housing material	ABS

Secvest Wireless Info Module

Art.-Nr. FUM050030

Seite 2 von 2

Technical data - Secvest Wireless Info Module

Integrated siren	Yes
Length	40.7 mm
Max. Air humidity	96 %
Max. Operating temperature	55 °C
Max. Receive range (building)	30 m
Max. Receive range (free field)	100 m
Mechanical protection	No
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Indoors
Mounting type	Surface mounted
Net weight	0.2 kg
PSTI conformity needed	No
Power consumption	0.48 W
Protection class IP	54
Radio frequency	868.6625 MHz
Security gradient	2
Sound pressure	90 dB
Tamper monitoring	No
VdS class	without
WEEE group	09
width	124 mm