

Smartvest Wireless Siren

Art.-Nr. FUSG35000A

Seite 1 von 2



To be able to provide alarming both indoors and outdoors, the Smartvest Wireless Siren is fitted with a loud siren (up to 100dB) and a red LED strobe light. Battery operation (battery life: up to two years) means no wiring is required during installation; when the battery is low, the alarm panel is notified immediately. To be able to guarantee real security, the Smartvest Wireless Siren is fitted with tamper protection in the form of an anti-removal wall contact.

Technologies

- Smartvest extension for sounding alarms indoors and outdoors
- Quick and cable-free installation without the need for wires thanks to battery operation
- High-volume siren (up to 100 dB) and red LED strobe light for alarms with deterrent effect
- Sturdy, weatherproof siren (IP44)
- Automatic supervision, with functional tests repeated daily and feedback sent to the Smartvest alarm control panel
- Low battery notification sent to the Smartvest alarm control panel
- Battery life of up to 2 years
- Tamper protection provided by anti-removal wall contact

Technical data - Smartvest Wireless Siren

Alarm generation	Acoustic warning signal
Areas of application	Outside / Inside
Battery - battery operation	Yes
Battery - max. battery life	1 years(s)
Battery - quantity	4
Battery type	C (1,5V)
Colour	White
Compatible with Secvest	No
Compatible with Smartvest	Yes

Smartvest Wireless Siren

Art.-Nr. FUSG35000A

Seite 2 von 2

Technical data - Smartvest Wireless Siren

Current consumption	200 mA
Current consumption standby	0.2 mA
DC power supply	5 V
Dimensions	(B x L x H) 112 x 122 x 300 mm
Gross weight	0.19 kg
Housing material	Plastic
Illuminant	LED
Light color	Red
Max. Air humidity	80 %
Max. Operating temperature	50 °C
Min. humidity	10
Min. operating temperature	-10 °C
Net weight	0.87 kg
PSTI conformity given	No
PSTI conformity needed	Yes
Plug type	DC-plug: 3,5 x 1,35mm
Product group	Detectors
Product security update min until	2024-12-31
Protection class IP	44
Radio frequency	868 MHz
Radio modulation	FSK
Radio range	(Depending on installation) 30 - 100 m
Sound pressure	100 dB
Tamper protection	Yes
Transmission power	4,5 dBm
WEEE group	09