

USB Keyboard for ABUS CMS

Art.-Nr. TVAC26010

Seite 1 von 2



Conveniently control your PTZ cameras from your PC with ABUS CMS software.

Using the USB keypad, you can control up to 64 PTZ cameras being displayed in ABUS CMS at the same time. The three-axis joystick ensures precise yet quick control of different angles of view and zoom functions in the camera's live cast. Configurable buttons and shortcut keys allow you to call up preset positions and tours, take snapshots and much, much more.

Accurate responses via remote access

The keypad enables you to respond quickly to events from your PC via remote access - allowing you, for example, to focus on one sector of the partition or visually track suspicious individuals.

Ideal for use in monitoring stations or for monitoring branches

The keypad is connected to a PC, which acts as the alarm control panel. The ABUS CMS allows you to access cameras from up to 256 recorders integrated on-site - and its keypad can then control all connected cameras.

Straightforward installation, universal compatibility

The keypad is connected to the PC via a USB cable and is ready to use straight away thanks to Plug&Play. Power is supplied from the PC directly via the USB cable. All recorders integrated into the ABUS CMS (DVR/NVR) can be accessed, as can all controllable cameras.

Technologies

- Simple PTZ control of cameras with ABUS CMS software
- 3-axis joystick (horizontal/vertical/rotation)
- 15 freely configurable buttons for presets/patrols and other functions
- 2 shortcut buttons on the control handle for taking snapshots
- Power supply and data transmission via USB
- Plug and play installation via USB port

USB Keyboard for ABUS CMS

Art.-Nr. TVAC26010

Seite 2 von 2

Technical data - USB Keyboard for ABUS CMS

Colour	Other
Connectable devices	ABUS CMS
Connection type	USB 2.0
Depth	116 mm
Dimensions	167 x 177 x 116 mm
Gross weight	0.65 kg
Height	116 mm
LED display	4-digit segment display, status LED
Language Manual	DE, EN
Length	177 mm
Max. Air humidity	90 %
Max. Operating temperature	55 °C
Min. operating temperature	-10 °C
Mounting type	Other
Net weight	0.588 kg
PSTI conformity needed	No
Power consumption	5 W
Product group	Accessories
Touchpanel	No
VdS class	without
WEEE group	09
width	167 mm