

ABUS Wired Indoor Siren

Art.-Nr. AZSG10020

Seite 1 von 2



The inside siren is installed inside your building. It is the last and critical module of a complete alarm chain. The inside siren is an acoustic signal generator. You have a choice between two alarm modes in this case. Both signals are felt to be extremely loud due to the high acoustic pressure and the signal frequency. The remotely activated LED of the alarm siren can be used to detect the status of the alarm panel (armed/disarmed). The rugged plastic housing of the acoustic signal generator is protected against sabotage by a wall and cover contact. The inside siren is powered with 12 V.

Technologies

- LED to display armed/disarmed status
- Simple, inconspicuous design
- Simple installation
- 90 dB(A) sound pressure @ 1m
- Tamper detection for front and rear sides
- Shock-resistant construction from polycarbonate

Technical data - ABUS Wired Indoor Siren

Colour	white
Compatible with	Secoris, Secvest, Terxon
Current consumption	100 mA
DC power supply	12 V
Dimensions	(WxHxD) 115x138x36 mm
Environmental class	II
Gross weight	0.212 kg
Height	41 mm
Housing material	POLYCARBONAT (PC)

ABUS Wired Indoor Siren

Art.-Nr. AZSG10020

Seite 2 von 2

Technical data - ABUS Wired Indoor Siren

Illuminant	LED
Length	145 mm
Max. Air humidity	95 %
Max. Operating temperature	40 °C
Mechanical protection	No
Min. operating temperature	-15 °C
Mounting location	Indoors, Wall
Net weight	0.174 kg
PSTI conformity needed	No
Power	1.2 W
Power consumption	1.2 W
Product group	Sirens and sounders
Sound pressure	90 dB
Tamper monitoring	Yes
VdS class	without
WEEE group	09
width	119 mm