

ABUS Z-Wave Smoke detector

Art.-Nr. SHRM10000

Seite 1 von 2



The ABUS Z-Wave smoke detector reliably warns of life-threatening smoke emission and sounds the alarm. However, the alarm is not limited to the detector itself. Even if you are not at home, the connected gateway informs you about an imminent threat at home. In combination with the ABUS Z-Wave LED lamps, you can also illuminate the escape route in the event of a fire and use other components to direct the correct reaction to the imminent threat in your home. The ABUS Z-Wave smoke detector also performs its service without a gateway, i.e. in stand-alone operation. With a battery life of up to 5 years, the detector also impresses with its extremely low requirements of maintenance.

Technologies

- Provides reliable warning of risk of potentially fatal smoke inhalation and sounds an alarm
- Compact design without compromising function
- Low maintenance thanks to 5-year battery life – integrated low battery warning
- Recommended installation locations: bedrooms, living rooms, children's rooms and hallways
- The source of the fire can be quickly and precisely identified using the app
- Includes test button for manual self-testing, for test alarms and temporary muting
- Fast and clean installation with no need for drilling

Technical data - ABUS Z-Wave Smoke detector

Alarm generation	Acoustic warning signal
Alarm muting	10 min
Areas of application	Inside
Battery - battery operation	Yes
Battery - max. battery life	5 years(s)
Battery - permanently installed	No
Battery - quantity	1

ABUS Z-Wave Smoke detector

Art.-Nr. SHRM10000

Seite 2 von 2

Technical data - ABUS Z-Wave Smoke detector

Battery type	CR123A (3V)
Colour	White
Compatible with Secvest	No
Compatible with Smartvest	No
Current consumption	90 mA
Current consumption standby	0.01 mA
Detection method	Photoelectric Reflection
Dimensions	(Ø x H) 60 x 49 mm
Display type	LED
Gross weight	0.239 kg
Housing material	Plastic
Max. Air humidity	95 %
Max. Operating temperature	40 °C
Min. humidity	10
Min. operating temperature	0 °C
Net weight	0.066 kg
PSTI conformity given	No
PSTI conformity needed	Yes
Radio frequency	868.42 MHz
Radio modulation	Z-Wave Plus (S2) / FSK (BFSK / GFSK)
Radio range	(Depending on installation) 20 - 100 m
Sensor type	Photodiode
Sound pressure	85 dB
Tamper protection	No
Transmission power	4,5 dBm