

IP Tube 8 MPx (4K, 2.8 mm)

Art.-Nr. IPCB68515A

Seite 1 von 4



4K 24/7 outdoor surveillance

The IP Tube provides video streams in 8 MPx resolution with up to 20 fps. The dust- and water-resistant IP67 housing is well suited for outdoor use. Due to integrated IR LEDs with a range of up to 50m, the camera can be used day and night. Access to the camera is possible at any time via app.

Universally applicable

The IP Tube IPCB68515A is designed for universal usage overlooking long distances due to the combination of IP67 weatherproof housing, 50m IR range and a 2.8 mm lens with a horizontal viewing angle of 102°.

Recording and compatibility

The recording can be done either on an ABUS recorder, 3rd party video management software or locally on a microSD card. Furthermore, the camera is compatible with the ABUS Secvest alarm center and the ABUS access control system wAppLoxx.

Comfortable installation

The IP Tube is mounted on the ceiling or optionally on the wall. We recommend the ABUS installation box (TVAC31350), which allows a protected cabling to wall or ceilings. The free "ABUS IP Installer" software is available for simple setup in the network. The software finds the camera quickly and easily within the network and supports during the installation process.

Note: The camera does not come with a power supply, as it can be powered via PoE.

IP Tube 8 MPx (4K, 2.8 mm)

Art.-Nr. IPCB68515A

Seite 2 von 4

Technologies

- 8 MPx (4K) Resolution: 3.840 x 2.160 @ 20 fps
- 2.8 mm fixed lens
- 120 dB WDR function to compensate for image contrasts
- Vandalism and weather protected housing (IK10 & IP67)
- IR LEDs (range up to 50m)
- Supports H.264, H.265, MJPEG (incl. dynamic GOP)
- microSD card slot for internal data storage
- 12 V DC & PoE (802.3at)

Technical data - IP Tube 8 MPx (4K, 2.8 mm)

Alarm generation	E-Mail, NAS, FTP
Aperture at minimum illumination (color)	F2.0
Application purpose	General surveillance
Article program	Professional
Backlight compensation	WDR, BLC, HLC
Camera type	Tube
Colour	RAL9003
Compatible with	NVR, Hybrid DVR, IPCam Plus
Compatible with ABUS Link Station	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes
Connections	1 x RJ45, 1 x DC
Construction type of device	Tube
Current consumption	792 mA
DC power supply	12 (+/-10 %) V
Day/night switching	ICR/Color/B/W
Dimensions	(LxWxH) 390x160x160 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/100000 s
Encryption	HTTPS
Focal length	2.8 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps
Height	160 mm
Horizontal viewing angle	102 °

IP Tube 8 MPx (4K, 2.8 mm)

Art.-Nr. IPCB68515A

Seite 3 von 4

Technical data - IP Tube 8 MPx (4K, 2.8 mm)

ICR day/night function	Yes
IR LEDs	Yes
IR range (up to)	50 m
Image optimization	WDR, BLC, HLC, 3D DNR
Image sensor	1/2.5" Progressive Scan CMOS
Language Manual	DE, UK, FR, NL, DK
Language OSD	DE, UK, FR, NL, DK
Length	390 mm
Lens	Fix
Lens mount	M12
Max. Air humidity	95 %
Max. Operating temperature	60 °C
Max. Resolution @ frame rate	3840 x 2160 @ 20 fps
Microphone	No
Min. operating temperature	-30 °C
Minimum illumination (IR)	0 lx
Minimum illumination (color)	0.01 lx
Motion detection	8 zones
Net weight	1.758 kg
Network bandwidth Video	32 kBit/s - 16 MBit/s
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ONVIF Profile S, ONVIF Profile G, ABUS Server, Secvest Link
Network connection	RJ45
Network connection LAN	RJ45 10M/100M self-adaptive
Noise suppression	3D DNR
Number of IR LEDs	10
Number of streams	3
Number of users	32
Other functions	Auto Backup Recording, Secvest Connectivity
PSTI conformity needed	No
Pixels (effective)	3840(H) x 2160(V)
PoE Standard	IEEE 802.3at
Power consumption	12.5 W
Privacy zones	4
Product group	Camera
Protection class IK	10
Protection class IP	67
Radio functions	Scene Change Detection
Resolution	8 MP

IP Tube 8 MPx (4K, 2.8 mm)

Art.-Nr. IPCB68515A

Seite 4 von 4

Technical data - IP Tube 8 MPx (4K, 2.8 mm)

Resolution modes	Stream 1: 3.840 x 2.160 @ 20 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1.280 x 720 @ 25 fps
Simultaneous network access	6
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	IE10, IE11, Mozilla Firefox 30.0+, Chrome 31.0+
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection
Video compression	Stream 1: H.264, H.265, Dynamic GOP, Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265, MJPEG
Video system	IP
WEEE group	09
White balance	AWB, Manual
width	160 mm