

4x analog HD signal distributor

Art.-Nr. TVAC25240

Seite 1 von 2



Use the 4x analog HD signal distributor to transmit the video input signal without loss to four monitors. Connect your camera to the signal distributor's video input and connect the monitors to the video outputs. Four BNC video outputs are provided.

Technologies

- Supports high resolutions up to 8MPx (4K) without video loss
- Transmission of a video signal to up to four monitors or recorders
- Suitable for HD-TVI, AHD, HDCVI, 960H, NTSC, PAL
- Channel 4 supports HD video + data control signal (UTC - Up The Coax)

Technical data - 4x analog HD signal distributor

Current consumption	110 mA
DC power supply	12 V
Depth	86 mm
Dimensions	(W x H x D) 138 x 30 x 86 mm
Height	30 mm
Language Manual	DE, GB
Language Packaging	DE, GB, FR, NL, DK, IT
Length	86 mm
Max. Air humidity	95 %
Max. Operating temperature	55 °C
Min. operating temperature	0 °C
Mounting type	Other
Net weight	0.12 kg
PSTI conformity needed	No
Product group	Accessories
Video input	1 BNC
Video input impedance	75 Ω
Video input level	1 Vpp dB
Video output	4 BNC
Video output level	1 Vpp
Video system	HD-TVI, HD-CVI, AHD, 960H, NTSC, PAL

4x analog HD signal distributor

Art.-Nr. TVAC25240

Seite 2 von 2

Technical data - 4x analog HD signal distributor

WEEE group	09
width	138 mm