

ABUS WiFi battery cam with base station

Art.-Nr. PPIC90000

Seite 1 von 4



Technical data - ABUS WiFi battery cam with base station

Article program	Comfort
Compatibility	Smartvest wireless system
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
Controllable with app	Yes
Location	Outdoor use, Interior
Max. number of video feeds	2
Net weight	0.424 kg
Operation mode	Solar, Rechargeable battery
PSTI conformity given	No
PSTI conformity needed	Yes
Power supply	Power adapter, Rechargeable battery
Radio functions	Night vision, 2-way audio, Zoom
Storage	Micro-SD
Technology	Electronics
WEEE group	09

Technical data - ABUS WiFi base station for WiFi battery cam

Article program	Comfort
Audio bit rate	128kbps
Audio compression	PCM
Audio input	Built-in Microphone
Audio output	Built-in Speaker
Base event	PIR motion detection / Manual

ABUS WiFi battery cam with base station

Art.-Nr. PPIC90000

Seite 2 von 4

Technical data - ABUS WiFi base station for WiFi battery cam

Colour	Black / white
Compatibility	Smartvest wireless system
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
Controllable with app	Yes
DC power supply	5 V
Dimensions	54 x 101 x 15 mm
Encryption	AES 128bit, WPA/WPA2-PSK
Frame rate	15
Frequency range	2,4 GHz
Gross weight	0.046 kg
Housing material	plastic
Location	Interior
Loudspeaker	85dB @ 10cm
Max. Air humidity	90 %
Max. Operating temperature	40 °C
Max. number of video feeds	2
Min. humidity	10%
Min. operating temperature	-10 °C
Net weight	0.093 kg
Network connection WLAN	802.11 b/g/n (2,4 GHz)
Number of channels	2
Number of users	3
PSTI conformity given	No
PSTI conformity needed	Yes
Power consumption	180 W
Power supply	Power adapter
Recording modes	max. 1080P
Resolution modes	VGA / 720p / 1080p
Storage	Micro-SD
Storage medium	microSD card up to 128 GB
Total video channels	2
Video compression	H.264
Video output	VGA / 720p / 1080p
WEEE group	09
EAN	4003318879142

ABUS WiFi battery cam with base station

Art.-Nr. PPIC90000

Seite 3 von 4

Technical data - ABUS Wi-Fi Battery Cam

Alarm generation	Push notification
Article program	Comfort
Audio bit rate	64kbps
Audio compression	g711
Audio input	Microphone
Audio output	Loudspeaker
Battery - runtime	up to 6 months (depending on local conditions) h
Battery type	2 x 18650 Li-Ion rechargeable batteries
Brightness White light LED	28 lm
Color temperature	3000 K
Colour	Black / White
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
DC power supply	5 V
DSP	Ingenic T30
Day/night switching	Auto
Dimensions	103 x 51 x 54 mm
Encryption	WPA2
Focal length	2,9 mm
Frequency range	2,4 GHz
Gross weight	0.277 kg
Horizontal viewing angle	115 °
Housing material	Plastic
Image sensor	Sony IMX307
Lens mount	5G
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Max. Resolution @ frame rate	Full HD (1080p) @ 15fps
Microphone	Yes
Min. humidity	10%
Min. operating temperature	-20 °C
Minimum illumination (color)	1 lx
Network connection WLAN	Wi-Fi (2,4GHz)
Network protocols	802.11 b/g/n
Number of users	3
PIR range	8 m
PIR viewing angle	112 °
Plug type	microUSB

ABUS WiFi battery cam with base station



Art.-Nr. PPIC90000

Seite 4 von 4

Technical data - ABUS Wi-Fi Battery Cam

Protection class IP	65
Radio range	depending on local conditions: 10-30 m
Rechargeable battery	Yes
Recording modes	PIR motion detection / Manual
Resolution modes	VGA / 720p / 1080p
Simultaneous network access	3
Software	App: ABUS App2Cam Plus (Android/iOS)
Storage medium	Micro SD Card, up to 128G
Vertical angle of view	75 °
Video compression	H.264
WEEE group	09
White balance	AWB
White light LEDs	1 St.
EAN	4043158185362