

WLX Pro Wall Reader-Set IP44 Access black

Art.-Nr. ACSE00012

Seite 1 von 2



The wAppLoxx Pro Wall Reader ideally expands the digital access system's use cases with closing and locking technology. Electronic door openers, motorised locks, electronic barriers or gates: the wall reader reliably controls all important access points. The special added value: the wall reader can be accessed via app as part of the wAppLoxx Pro system - allowing electronic garage doors or already installed motorised locks, for example, to be controlled intelligently at any time through the app - even while on the go. The high-quality, scratch-resistant glass front serves to identify access authorisations by reading in the locking medium and provides feedback to the user in the form of visual and acoustic signals.

Technologies

- Ideal for controlling electronic door and gate drives, door openers, lifts, barriers, rolling grilles, turnstiles
- Encrypted AES 128-bit data transfer between wAppLoxx Pro Wall Reader, Bridge Box and Control
- Other jumper settings, e.g. control of the 2nd relay in case of tampering, Wall Reader mute switching, pulse, delay, etc.
- Bus cable (5-core) already included in the scope of delivery with the reader (6m)
- Optical and optional alarms

Technical data - WLX Pro Wall Reader-Set IP44 Access black

Article abbreviation	WLX-PRO-Set-WR-A-S
Closing media	Mifare DESfire EV1, Mifare DESfire EV2, Mifare Classic
Colour	black
Depth	17 mm
Height	86 mm
Max. Operating temperature	40 °C
Min. operating temperature	-10 °C
Mounting type	Surface mounted
Net weight	0.874 kg
PSTI conformity given	Yes
PSTI conformity needed	Yes

WLX Pro Wall Reader-Set IP44 Access black

Art.-Nr. ACSE00012

Seite 2 von 2

Technical data - WLX Pro Wall Reader-Set IP44 Access black

Product security update min until	2030-12-31
Programming 1	Configuration and system administration via wAppLoxx Pro Control
Radio networked	Yes
Standalone	No
VdS class	without
WEEE group	09
width	110 mm

Technical data - WLX Pro Bridge Box Access

Areas of application	Indoor
Article abbreviation	WLX-PRO-BB-A
Colour	white
Connections	1 external input
DC power supply	3 A / 12 V
Dimensions	100 x 135 x 30 mm
Housing material	PVC
Max. Air humidity	80 %
Net weight	0.2 kg
Radio frequency	868.3 MHz
Radio range	up to 30 m indoors / free field nominal 100 m
WEEE group	09
EAN	4043158169461

Technical data - WLX Pro Wall Reader IP44 black

Areas of application	Indoor and sheltered outdoor use
Colour	black
Connections	BUS
Dimensions	110 x 86 x 17 (Gira frame) mm
Housing material	PVC with genuine glass
Max. operating temperature	60 °C
Min. operating temperature	-25 °C
Net weight	0.38 kg
Protection class IP	44
EAN	4043158160000