

External housing for frame surface mounting (1 module)

Art.-Nr. TVHS20160

Seite 1 von 2



TOTAL MODULAR: THE VIDEO INTERCOM SYSTEM

See people in front of the door, talk to them, open the door. Modularly adaptable to any building and easy to install - well protected with the appropriate external housing.

Robust and safe in any weather: your ModuVis installation

When installing ModuVis modules (video module, bell button module, etc.), you can choose between surface and flush mounting. In the case of surface mounting, the external housing is recommended as a robust protection against penetrating moisture. This external housing is suitable for the single mounting frame (1 module).

Totally modular, extensively expandable

A clear advantage: depending on the number of flats or living areas and local requirements, modules are simply added to the system, e.g. info module with name plate, bell button module or numeric keypad for keyless access via PIN code. When attaching the modules, it is always possible to surface-mount or flush-mount them, depending on the installation frame used.

Technologies

- External housing for frame surface mounting (1 module) for the ModuVis door intercom system
- Extended weather protection for outdoor installation

External housing for frame surface mounting (1 module)

Art.-Nr. TVHS20160

Seite 2 von 2

Technical data - External housing for frame surface mounting (1 module)

Colour	aluminum
Depth	58 mm
Dimensions	115 x 122 x 58 mm
Height	122 mm
Mounting type	Surface mounted
Net weight	0.325 kg
PSTI conformity needed	No
Product group	Video
width	115 mm