

Day/Night Mini Outdoor Dome Camera

Art.-Nr. TVCC34011

Seite 1 von 2



Unobtrusive monitoring indoors or outdoors

The analogue day/night outdoor dome camera is the ideal supplement to the TWR33601 4-channel recorder and the TVVR33620D/T video surveillance kit. It stands out with its plain design and high protection class (IP67), which means it can be used both outdoors and indoors. The camera has integrated IR LEDs for 24/7 use both day and night. With a high, detailed resolution of 600 TVL, it delivers precise video images for accurate recognition of persons.

Flexible mounting options

Fast and easy installation is guaranteed with the 30 m combination cable and power supply unit provided.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- Compact day/night vision mini outdoor dome camera
- Varied camera installation options - whether indoors or outdoors
- Simple design and high protection class (IP67)
- High detailed resolution, thanks to 600 TVL
- 1 x 30 metre coaxial cable included
- Ideal for extension of TVVR33601 or TVVR33620D

Day/Night Mini Outdoor Dome Camera

Art.-Nr. TVCC34011

Seite 2 von 2

Technical data - Day/Night Mini Outdoor Dome Camera

Article program	Performance
Colour	white
Construction type of device	Dome
Current consumption	400 mA
DC power supply	12 V
Day/night switching	Electromechanical IR-cut filter
Depth	90 mm
Diameter	90 mm
Dimensions	90 x 90 x 68 mm
Focal length	2,8 mm
Gross weight	1.3 kg
Height	68 mm
Horizontal viewing angle	75 °
IR LEDs	Yes
IR range (up to)	20 m
Image sensor	1/2.8" Progressive Scan CMOS
Length	90 mm
Lens	Fixed
Max. Air humidity	90 %
Max. Operating temperature	60 °C
Min. operating temperature	-20 °C
Minimum illumination (IR)	0 lx
Minimum illumination (color)	0.1 lx
Net weight	0.4 kg
PSTI conformity needed	No
Power consumption	4.8 W
Product group	Video
Protection class IP	67
Radio networked	No
Resolution	720 x 480
TVL	600
Video motion detector included	No
Video output	1.0 Vss
WEEE group	09
White balance	Auto
width	90 mm