

SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



Technologies

- Distance of cams adjustable to most common drilling patterns
- Handle on inside automatically returns to initial position
- Fixing screws hidden by decorative aluminium plate
- For cylinder protrusions of 12 mm
- Spacing: 92 mm, square bolt: 8 mm
- Easy fitting

Operation and use

- For universal use on narrow frames
- Grip plate outside, handle inside
- Suitable for door thicknesses of 57 - 65 mm

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), stainless steel look, white
- Alternatively available as a handle/handle set

Technical data - SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	12 mm
Distance measure	92 mm
Door fitting for fire doors	No
Door type	Doors with tubular frames
Interchangeable fitting	Yes
Security Level Home Security	5

SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

Technical data - SRG92N for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Weight	1074 g
colour	F1: Aluminum Nature
pulling protection	No
EAN	4003318625541

