

SRG72N for flat entrance doors in F1: Aluminum nature (Handle plate/Door handle)

Seite 1 von 2



SECURITY FOR NARROW FRAME DOORS

This door fitting secures your flat entrance door.

Flat entrance doors are always an object of desire for burglars. Since these are often inadequately secured, criminals often have an easy time of it. Door cylinders often protrude somewhat and can therefore be easily removed by force. Protect yourself against this break-in method with a reliable door fitting. This door fitting has been specially developed for flat entrance doors with a narrow frame profile and a door thickness of 57 to 65 millimetres. It has an automatic lever handle reset mechanism in the inside shield and cams that are variably adjustable to most common hole patterns. This makes assembly child's play.

Technologies

- Cam spacing variably adjustable to most common hole patterns
- Automatic lever handle reset mechanism in the inside shield
- Mounting screws concealed by decorative aluminium shield
- for cylinder protrusion of 12 mm
- Distance measurement: 72 mm, square bolt: 8 mm
- Easy mounting

Operation and use

- For universal use on narrow frame doors
- Suitable for door thicknesses from 57 - 65 mm

Variants

SRG72N for flat entrance doors in F1: Aluminum nature (Handle plate/Door handle)

Seite 2 von 2

- Colours: F1 (alu anodized), white
- Available as a handle set and two handles set

Technical data - SRG72N for flat entrance doors in F1: Aluminum nature (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	12 mm
Distance measure	72 mm
Door type	Doors with tubular frames
Interchangeable fitting	Yes
Security Level Home Security	5
Weight	1132 g
colour	F1: Aluminum Nature
pulling protection	No
EAN	4003318952012