

ABUS EasyLook Camera



Art.-Nr. PPDF17520X

Seite 1 von 2

Technical data - ABUS EasyLook Camera

Article program	Comfort
Base event	PIR & Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
DC power supply	12 V
Day/night switching	Auto
Dimensions	(W x L x H) 61 x 161 x 77 mm
Encryption	WPA2
Focal length	4 mm
Frequency range	2,403 - 2,478 GHz
Horizontal viewing angle	82 °
Housing material	Plastic
IR LEDs	Yes
IR range (up to)	15 m
IR swivel filter	Yes
Image sensor	1/3" CMOS
Loudspeaker	Yes
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Max. Resolution @ frame rate	2305 x 1296 @15fps
Microphone	Yes
Min. humidity	30
Min. operating temperature	-10 °C
Minimum illumination (IR)	0.1 lx
Minimum illumination (color)	1 lx
Optical wavelength	940
PIR range	8 m
PIR viewing angle	85 °
Plug type	DC-plug: 5,5 x 2,1 mm
Power consumption	3.6 W
Privacy zones	4
Protection class IP	66
Radio range	(Depending on installation) 20 - 50 m
Resolution modes	2305 x 1296 (3MP)

ABUS EasyLook Camera



Art.-Nr. PPDF17520X

Seite 2 von 2

Technical data - ABUS EasyLook Camera

Sensitivity	-88 dBm
Transmission power	20 dBm
Vertical angle of view	42 °
Video bitrate	2Mbps
Video compression	H.264+
White balance	Auto