

# WLX Pro Bridge Box Intrusion

Art.-Nr. ACPA00001

Seite 1 von 1



## Technologies

- Ideal for controlling electronic door and gate operators, door buzzers, elevators, barriers, rolling grilles, turnstiles
- Control unit for the wAppLoxx Pro Wall Reader
- High level of protection against tampering due to separate mounting from the reader unit in the secured interior area
- Arming and disarming of intrusion detection systems (intrusion variant)
- Encrypted AES 128-bit data transmission to the wAppLoxx Pro Wall Reader via BUS
- Encrypted AES 128-bit wireless data connection to the wAppLoxx Pro Control
- External input enables switching of a relay e.g. for switches, pushbuttons, ...
- Further jumper settings e.g. control of the 2nd relay in case of sabotage, mute circuit Wall Reader, pulse, delay, ...

## Technical data - WLX Pro Bridge Box Intrusion

|                      |                                               |
|----------------------|-----------------------------------------------|
| Areas of application | Indoor                                        |
| Article abbreviation | WLX-PRO-BB-I                                  |
| Colour               | white                                         |
| Connections          | 1 external input                              |
| DC power supply      | 3 A / 12 V                                    |
| Dimensions           | 101 x 135 x 30 mm                             |
| Housing material     | PVC                                           |
| Max. Air humidity    | 80 %                                          |
| Net weight           | 0.2 kg                                        |
| Radio frequency      | 868.3 MHz                                     |
| Radio range          | up to 30 m indoors / free field nominal 100 m |
| WEEE group           | 09                                            |