

Active glass break alarm VdS C

Art.-Nr. AZGB10100

Seite 1 von 3



DETECTS GLASS BREAKAGE & TAMPERING

Sensitive & secure

The active glass break alarm detects any change to window panes or glass surfaces with high sensitivity. It reports any deviation to the Secoris intrusion alarm control panel. The automatic self-test avoids false alarms, even if there is dirt on the pane. The glass break alarm consists of an ultrasonic transmitter, receiver and evaluation unit.

Active ultrasound monitoring

The piezo transmitter element causes the glass pane to vibrate by means of an ultrasonic signal, which is picked up by the piezo receiver element. Both compact elements are simply and inconspicuously placed on the pane and are wired to the evaluation unit, which determines the condition of the pane. If the transmitted frequency has changed on its way across the pane, an alarm is triggered.

All-rounder: monitors practically all glass types

Almost all types of glass in frame constructions can be monitored with the active glass break alarm. In addition to window, crystal, tempered and insulating glass, also bullet-proof, laminated and safety glass, as well as glass with a wire insert or shatter protection film. The alarm is certified according to VdS C and is suitable for protecting areas with high security standards (e.g. museums).

Versatile compatibility

The wire glass break alarm can be used with the ABUS Secoris intrusion alarm system and other alarm systems with wire detector groups (wire zones), such as ABUS Terxon or Secvest.

Technologies

- Reliably monitors glass surfaces for destruction (glass breakage, glass cutting) and tampering
- Active, highly sensitive ultrasound monitoring (frequency, time interval and reflection measurements) between

Active glass break alarm VdS C

Art.-Nr. AZGB10100

Seite 2 von 3

transmitter and receiver, each wired to the evaluation unit

- Absolutely flexible, highly secure: suitable for a wide variety of glass types in frame constructions, such as window, crystal, tempered, insulating, bullet-proof, laminated, safety glass as well as glass with wire inlay or shatter protection film
- Highest real alarm precision (reliable false alarm protection) and maintenance-free operation due to automatic self-test (no readjustment, no false alarms due to dirt on the pane)
- Suitable for all windows, window doors, building glazing and areas/installations with high security requirements (e.g. bullet-proof glass, display cases, museums)
- Unobtrusive monitoring and low installation effort: mounting of the compact transmitter and receiver unit on the glass pane (inside), with connection cable to the evaluation unit
- Low power consumption
- Finish: white
- VdS C certified: VdS Class C (G 188149)

Technical data - Active glass break alarm VdS C

Adjustable sensitivity	Normal glass / laminated glass and bulletproof glass
Alarm memory	Yes
Areas of application	Windows
Cable length	6 m
Cable style	LiYCY 1 x 0,14 mm ² (1,8 mm)
Certifications	VdS C
Colour	*Unnamed (Identifier: Weiß)
Compatible with	Secoris
Connection cable length	600 cm
Current consumption	18 mA
Current consumption standby	22 mA
DC power supply	10,4 - 15 V
Depth	30 mm
Detection method	Ultrasonic
Display type	LED
Environmental class	II
Gross weight	0.46 kg
Height	110 mm
Housing material	stainless steel
Length	30 mm
Max. operating temperature	75 °C
Min. operating temperature	-10 °C
Net weight	0.46 kg
PSTI conformity needed	No

Active glass break alarm VdS C

Art.-Nr. AZGB10100

Seite 3 von 3

Technical data - Active glass break alarm VdS C

Power consumption	0.22 W
Product group	Detectors
Status display	Yes
Tamper monitoring	Yes
Type of protection	Intrusion protection
VdS approval no.	G 188149
VdS class	C
WEEE group	09
width	90 mm