

Keypad Terxon SX - 2023

Art.-Nr. AZBE10000

Seite 1 von 2



The LCD control panel is an extension module for the Terxon SX. Mounted near the entrance, it allows you to operate your alarm control panel quickly. The LCD control panel is connected to the Terxon SX via 4-wire bus wiring. Up to 4 control panels can be integrated into the alarm system. Installed in different parts of your building, these extension modules provide additional convenience. The system can be conveniently activated or deactivated from each control panel using a PIN code. The status of the alarm panel is also shown on the control panel's plain text display. System settings, programming and the 350-fold event memory of the Terxon SX can be viewed - and of course changed - at your leisure. The LCD control panel is an elegant white colour.

Technologies

- For operating and programming the Terxon SX alarm control panel
- For convenient arming/disarming of the alarm panel using a PIN code when leaving/entering the building
- Operating the alarm panel with PIN code and four-way navigation button
- Coloured LEDs to display the current system status

Technical data - Keypad Terxon SX - 2023

Certifications	without
Colour	weiß
Connections	RS485 BUS, Screw terminal für additional tamper contact
Current consumption	58 mA
DC power supply	12 V
Depth	29 mm
Dimensions	(WxHxD) 128x128x29 mm
Environmental class	II
Height	128 mm
Housing	ABS

Keypad Terxon SX - 2023

Art.-Nr. AZBE10000

Seite 2 von 2

Technical data - Keypad Terxon SX - 2023

Integrated siren	Yes
Length	29 mm
Max. Air humidity	93 %
Max. Operating temperature	55 °C
Min. operating temperature	-10 °C
Mounting location	surface mount
Net weight	0.212 kg
Number of rooms / groups	1
PSTI conformity needed	No
Product group	Control units
Switching outputs	No
Tamper monitoring	Yes
VdS class	without
WEEE group	09
width	128 mm