

Additional pan/tilt camera for ABUS EasyLook BasicSets

Art.-Nr. PPDF17620

Seite 1 von 3



Up to four cameras per monitor

Add up to 4 cameras to your ABUS EasyLook BasicSet. Commissioning an additional pan/tilt camera is just as easy as with the basic set and done in just a few steps.

Just like the camera in the basic set, an additional camera reliably delivers video images day & night. The security camera performs its job without internet/Wi-Fi, without an app and without a smartphone - all it needs is power. The video data and settings are securely encrypted and quickly transmitted wirelessly between the security camera and the monitor of the basic set.

Commissioning the additional camera is just as easy as with the basic set. A total of up to 4 cameras can be easily operated with one monitor; if needed, the screen displays all live images from the cameras simultaneously - with a simple finger gesture, it is possible to quickly switch between the "quad view" and individual camera images.

So you always have a view of what is happening in your shop or around your home, whether at the entrance, in front of the garage, on the terrace or in the garden.

Technologies

- Extension for the ABUS EasyLook BasicSet; additional pan/tilt camera with high wireless range, person detection, intercom function, night vision, privacy zone masking and much more
- A total of 4 security cameras (with/without pan/tilt function) can be connected to the monitor of the ABUS EasyLook BasicSet
- Very easy to use, even for subsequent commissioning; supply power to the additional camera, add it to the set monitor and the first live image will appear
- Set up surveillance camera just the way you like it on the monitor: Standard motion detection or person detection only, deactivate audio/sound for recordings, image areas with/without recognition, schedules, privacy zones and

Additional pan/tilt camera for ABUS EasyLook BasicSets

Art.-Nr. PPDF17620

Seite 2 von 3

more.

- Clear night vision in black and white (via infrared LED) up to 15 metres, 3-megapixel camera resolution, zoom function, 82-degree viewing angle, camera protection class IP66 (weatherproof; protection against strong jets of water, dustproof)
- The EasyLook BasicSet Monitor immediately and automatically switches to alarm and recording mode (siren sound on the monitor can be switched on/off as required)
- No further costs (no subscription, no cloud)

Technical data - Additional pan/tilt camera for ABUS EasyLook BasicSets

Areas of application	Outdoor use
Article program	Comfort
Base event	Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000; PPDF17100
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Controllable with app	No
DC power supply	12 V
Day/night switching	Auto
Depth	210 mm
Dimensions	210 x 120 x 160 mm
Encryption	WPA2
Focal length	4,1 mm
Frequency range	2,403 - 2,478 GHz
Height	160 mm
Horizontal viewing angle	85 °
Housing material	Plastic
IR LEDs	Yes
IR range (up to)	15 m
Image sensor	1/3" CMOS
Location	Outdoor use
Loudspeaker	Yes
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Max. Resolution @ frame rate	2304 x 1296 @15fps
Microphone	Yes

Additional pan/tilt camera for ABUS EasyLook BasicSets

Art.-Nr. PPDF17620

Seite 3 von 3

Technical data - Additional pan/tilt camera for ABUS EasyLook BasicSets

Min. humidity	30
Min. operating temperature	-10 °C
Minimum illumination (IR)	0.1 lx
Minimum illumination (color)	1 lx
Net weight	0.814 kg
Optical wavelength	940
PSTI conformity needed	No
Pan/tilt range	270° / 90°
Plug type	DC-plug: 5,5 x 2,0 mm
Power consumption	3.75 W
Power supply	Power adapter
Privacy zones	4
Product group	Video sets
Protection class IP	66
Radio functions	Intercom (2-way audio), People recognition, Zoom, Night vision
Radio networked	Yes
Radio range	(Depending on installation) 20 - 50 m
Resolution modes	2304 x 1296 (3MP)
Sensitivity	-88 dBm
Transmission power	20 dBm
Vertical angle of view	45 °
Video bitrate	2Mbps
Video compression	H.264+
Video motion detector included	Yes
WEEE group	09
White balance	Auto
width	120 mm