

Secoris wireless motion detector PIR MW

Art.-Nr. FUBW60120

Seite 1 von 2



Technical data - Secoris wireless motion detector PIR MW

Animal immune	<25 kg
Areas of application	Interior
Battery - max. battery life	5 years(s)
Battery - permanently installed	No
Battery - quantity	3
Battery type	1,5V AA
Certifications	EN 50131 Grade 2
Colour	white
Compatible with	Secvest, Secoris
Cover monitoring	No
Current consumption standby	0.02 mA
DC power supply	4,5 V
Depth	55 mm
Detection area detector (m)	10 m
Detection method	Heat detection, Microwave
Diameter	55 mm
Dimensions	55x115x55 (BxHxT) mm
EN	Level 2
Environmental class	II
Frequency band	24 GHz
Gross weight	0.194 kg
Height	115 mm
Housing material	ABS

Secoris wireless motion detector PIR MW

Art.-Nr. FUBW60120

Seite 2 von 2

Technical data - Secoris wireless motion detector PIR MW

Language Manual	DE, EN; FR; NL; DK; IT
Language Packaging	DE, EN; FR; NL; DK; IT
Length	55 mm
Max. Air humidity	95 %
Max. Operating temperature	55 °C
Max. Transmit range (free field)	700 m
Max. Transmitting range (building)	30 m
Mechanical protection	No
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Wall
Net weight	0.17 kg
PIR viewing angle horizontal	85 °
Product group	Detectors
Radio frequency	868.09 MHz
Radio frequency 2	868.23 MHz
Radio frequency 3	868.37 MHz
Radio frequency 4	868.51 MHz
Radio frequency 5	868,6625 MHz
Radio power	10 mW
Rechargeable battery	No
Security gradient	2
Sensor type	PIR, Microwave
Tamper monitoring	Yes
Technology	Electronics
Type of protection	Intrusion protection
VdS class	without
Voltage monitoring	Yes
WEEE group	09
width	55 mm