



NOTIFICATION CALL: ALARM & ALARM SYSTEM STATUS TRANSMISSION TO PHONE

The dialler for voice and text messages connects the alarm system (wireless/wired) to the telephone network. If the alarm panel sends an alarm or status message, the dialler transmits this as a voice or text (call/text message with stored wording) to a landline or mobile phone.

Silent alarm via telephone.

If the alarm system triggers a silent alarm, the dialler forwards this to the telephone. 8 events (e.g. burglary, hold-up, medical emergency, fire) are available via wired input, each of which is assigned an event text (SMS, voice).

8 messages to 10 numbers - via mobile network (GSM/UMTS/LTE)

In the event of an alarm, the respective event text is sent to a maximum of 10 contacts.

Remote access, on-site interaction, mailbox

Messages can be retrieved or the device programmed while on the move via a call. Listening and speaking mode (microphone/speaker) allows you to listen/speak into the building. And the mailbox forwards incoming text messages, e.g. when the prepaid SIM card runs out of credit.

Stand-alone operation, 4 switching outputs

Signals from systems other than an alarm system are also processed via wired inputs. This means that other devices can also be controlled via 4 switching outputs - e.g. for home automation or industrial applications.

Technologies

- Enables communication via the mobile network
- Text and voice messages via mobile network (GSM/UMTS/LTE)

- Alarm and status messages to up to 10 stored phone numbers
- Communication path (GSM/UMTS/LTE) for maximum transmission reliability
- Remote access via telephone for worldwide operation while on the move
- Integrated listening and speaking mode for easy on-site interaction
- Mailbox function for forwarding messages (e.g. prepaid credit)
- Can be used independently of an alarm panel (home automation, industry)

Technical data - GSM/UMTS/LTE-Dialer

Compatible with	Secoris, Secvest
Connections	Screw terminal for power supply
Current consumption	50 mA
DC power supply	10,5-28 V
Dimensions	(WxHxD) 150x115x30 mm
Display type	Illuminated segment display
Height	115 mm
Housing material	ABS
Inputs	8
Language Manual	6 languages (UK, DE, FR, NL, DK, IT)
Language OSD	6 languages (UK, DE, FR, NL, DK, IT)
Language Packaging	6 languages (UK, DE, FR, NL, DK, IT)
Length	30 mm
Max. Operating temperature	55 °C
Min. operating temperature	-10 °C
Net weight	0.37 kg
Number of voice messages	8
Outputs	4 transistor outputs (OP), negative switching, max. current output 100 mA / 12 V DC per output
Programming 1	Menu
Protection class IP	32
Recording duration	0.075 h
Remote access	Yes
Tamper monitoring	Yes
Telephone numbers Memory locations	10
Transmission path	GSM/UMTS/LTE
Transmission type	Language, SMS
Type of inputs	Positive/negative controllable inputs (5-24 V DC)
VdS class	without
Voltage monitoring	Yes

Art.-Nr. AZWG10030

Seite 3 von 3

Technical data - GSM/UMTS/LTE-Dialer

WEEE group	09
width	150 mm