

TECTIQ double knob cylinder, reader both sides CH

Art.-Nr. TEC-Z-CH-LB

Seite 1 von 3



SIMPLE. ACCESS. ORGANISATION.

With the digital TECTIQ locking system.

The electronic TECTIQ locking cylinder with RFID reader grants people access on the locking medium (transponder, card) according to their permission level. Data exchange is encrypted and protected against readout (MIFARE® DESFire®). The battery-operated door component requires no external cabling or radio connection.

Validation/update

ABUS TECTIQ stores permissions and events on the RFID locking medium (Data-on-Card) and exchanges data wirelessly with the cylinder or the system. The optical illuminated ring signals to users whether they are authorised to access the system.

Elegant design, top quality

With its clear design and knob caps (RFID reader unit) in black or grey, the robust, high-quality cylinder with IP67 and stainless steel look is suitable for any door and surface.

Custom cylinder length

The double knob cylinder is suitable for exterior and interior doors with door leaves 32.5 to 57.5 mm thick on each side. Can be ordered in fixed lengths in 5 mm increments to adjust length to individual conditions.

Wide range of variants

Available in different versions: with reader on the outside or on both sides (e.g. for connecting doors), as a double knob, half cylinder or padlock.

Technologies

- Electronic TECTIQ double knob cylinder (Switzerland round) for secure, simple and flexible installation on almost all connecting doors (solid leaf, profile frame, timber, aluminium, steel, plastic)
- High-quality cylinder (RFID reader on both sides) with stainless steel outside knob and continuous stainless steel look, in a discreet, purist design line; highly weather-resistant in the standard version (IP67)
- TECTIQ cylinder with RFID reader for secure, readout-protected Data exchange with TECTIQ locking media (MIFARE® DESFire®); with free-running exterior knob: no access without authentication
- The cylinder can be programmed via Bluetooth with the TECTIQ Admin app and, for example, receive a new time or

TECTIQ double knob cylinder, reader both sides CH

Art.-Nr. TEC-Z-CH-LB

Seite 2 von 3

the latest firmware update

- Elegant design in different Design variants to match the style of your building thanks to different colours and knobs
- Replace the cylinder instead of the fitting: convert a mechanical to an electronic cylinder at a favourable price and integrate the door into the TECTIQ locking system (simple cylinder replacement using a screw)
- Tested, certified quality: EN 15684 and fire protection T30

Technical data - TECTIQ double knob cylinder, reader both sides CH

Air humidity	20-99 % non-condensing according to EN 15684 class 4
Areas of application	Passage doors with authorization checks on both sides
Article abbreviation	TEC-Z-CH-LB
Article program	TECTIQ
Battery - runtime	At 20 °C (room temperature): up to 60,000 cycles or 3.5 years if not actuated h
Battery compartment	In knob
Battery type	VARTA Lithium battery 3V CR2/CR15H270/6206
Battery warning levels	2 levels
Bluetooth version	5.1
Certifications	EN 15684:2020 1-6-B-4-x-D-3-A/D
Colour	knob: brushed stainless steel black or grey / Cylinder body: brushed stainless steel
Construction type of device	Double knob cylinder
Corrosion protection	According to EN 1670 class 3/EN 15684 class 4
Cylinder profiles	Swiss round
Dimensions	knob: L = 48 mm, Ø = 38 mm
Drill protection	Security (EN 15684 Ziffer 8 Klasse D)
Emergency power supply	Yes, Micro USB
Extension steps	5 mm
Factory reset	Yes
Fatigue strength	> 200.000 cycles (EN 15684:2020 class 6)
Internal knob variants	Square / Round
Management	TECTIQ Access Manager
Material	cap: stainless steel, plastic / Cylinder body: brass
Max. External length	57.5 mm
Max. Internal length	57.5 mm
Max. Number of blacklists	120
Max. Operating temperature	65 °C
Memory type	Ring memory: 890 events
Min. external length	32.5 mm
Min. indoor length	32.5 mm
Min. operating temperature	-25 °C

TECTIQ double knob cylinder, reader both sides CH

Art.-Nr. TEC-Z-CH-LB

Seite 3 von 3

Technical data - TECTIQ double knob cylinder, reader both sides CH

Net weight	0.6 kg
Opening time adjustable	Yes (6/12 Sec)
Outside knob variants	Square / Round
Power supply	Rechargeable battery
Programming 1	TECTIQ System Cards, TECTIQ Admin App
Programming technology	RFID (13.56 MHz) / Bluetooth (2.4 GHz)
Protection class IP	67
RFID frequency	13.56 MHz
RFID range	≤ 1 cm
RFID technology	MIFARE® DESFire® EV1, EV2, EV3
Radio conformity	ETSI EN 300 328
Radio encryption	AES 128-Bit
Radio networked	Yes
Radio standard	Bluetooth Low Energy 2,4 GHz
Real-time clock (RTC)	Yes
Security features	Freely rotating outside knob to prevent unauthorized access, engagement only when an authorised locking medium is presented, predetermined breaking point on outside knob, drilling protection
Special functions	Office Mode
Special lengths	Yes, on request
Transmission power	-4 dBm
Transponder conformity	Passive-Transponder ISO 14443 A (MIFARE® DESFire®)
Transponder encryption	AES 128-Bit
Update capability	Yes (USB Updater Cable / Admin App)
backset	≥ 30 (round knob)/ ≥ 35 (square knob) mm
signaling	Visual