



Precise and clear. In 4K

This clever surveillance camera sends you accurate information, delivers ultra-sharp 4K recordings and comes with functions for intercom, alarm and much more

With other security cameras it is sometimes the case that they keep sending push notifications, but is the trigger even relevant to you? Instead of guessing, you should be able to rely on your surveillance camera. And in an emergency, it should provide clarity.

The SmartLook Pan & Tilt does exactly that: it distinguishes completely automatically between person, animal and vehicle. You decide what is important to you and only then will you receive a push notification via the App2Cam Plus mobile phone app. This saves time and saves nerves.

Another highlight: the camera delivers brilliant image quality day and night. It saves recordings in ultra-high resolution in 4K.

Incidentally, all functions are permanently available to you free of charge with the app: for example, to hide private and public areas and to turn the camera eye very quickly to a specific position. The same applies to access when on the go and the intercom function, e.g. for contactless communication with parcel couriers. With the included microSD memory card, the camera is ready to record immediately and the app even shows what happened up to 5 seconds before motion detection (pre-recording).

The smart security camera is ready to use immediately after extremely simple start-up, is completely weatherproof and therefore ideal for outdoor use. It has everything you need for operation compliant with data protection requirements. It is compatible with the Smartvest wireless alarm system. And also with the ABUS One app: there you can access the most important camera functions and operate many other smart devices from ABUS with just one app -

SmartLook Pan & Tilt

Art.-Nr. PPIC52520B

Seite 2 von 4

clever, reliable, convenient.

Technologies

- Smart and weatherproof pan & tilt surveillance camera with free mobile phone app, recordings in 4K/UHD resolution, night vision, intelligent motion detection and push notification, intercom function and much more
- Flexible outdoor placement: connected to your home network via Wi-Fi with high stability and range (2.4 or 5 GHz) or via LAN cable
- Customise all settings as required: Sensitivity of motion detector, image areas without detection, semi-automatic quick rotation via app to 3 definable positions (presets) etc.
- Data protection-compliant thanks to recording without sound, circular buffer and image areas blacked out as required (so-called private zones, also for public areas and neighbouring properties)
- Recordings in Ultra HD (8 megapixels), night vision up to 20 m, protection class IP66 (weatherproof)
- Also compatible with the Smartvest app & ABUS One

Technical data - SmartLook Pan & Tilt

Alarm generation	Push notification / E-Mail
Aperture	F2.0
Article program	Comfort
Audio bit rate	16 Kbit/s
Audio compression	AAC
Audio input	Microphone
Audio output	Loudspeaker
Automatic aperture control	Yes
Base event	Object detection + motion mask
Channel width	20 MHz
Colour	white
Compatibility	Smartvest wireless system
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
Construction type of device	PTZ
Controllable with app	Yes
DC power supply	5 V
Day/night switching	Auto
Depth	210 mm
Dimensions	210 x 120 x 160 mm
Encryption	AES 128bit, WPA/WPA2-PSK/ WPA3 (personal)

SmartLook Pan & Tilt

Art.-Nr. PPIC52520B

Seite 3 von 4

Technical data - SmartLook Pan & Tilt

Focal length	4 mm
Frequency range	2,400 –2,485 / 5,0 GHz
Height	120 mm
Horizontal viewing angle	85 °
Housing material	Plastic
IR LEDs	Yes
IR range (up to)	20 m
IR swivel filter	Yes
Image sensor	1/2.8" CMOS
Location	Outdoor use
Loudspeaker	Yes
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Max. Resolution @ frame rate	4K Ultra HD @ 15fps / Full HD (1080p) @ 15fps
Microphone	Yes
Min. humidity	20
Min. operating temperature	-10 °C
Minimum illumination (IR)	0 lx
Minimum illumination (color)	1 lx
Net weight	0.65 kg
Network connection	RJ-45 connector (10/100 Mbps)
Network connection WLAN	IEEE 802.11 b/g/n/ac/ax
Network protocols	TCP/IP, UDP, SMTP, NTP, DHCP, ARP
Number of presets	3
Number of users	3
Optical wavelength	940
PSTI conformity given	Yes
PSTI conformity needed	Yes
Pan/tilt range	270° Horizontal / 80° Vertical
Plug type	DC-plug: 3,5 x 1,35 mm
Power consumption	4 W
Power supply	Power adapter
Pre/post-alarm memory	up to 5 sec.
Privacy zones	3
Protection class IP	66
Radio functions	App control & remote access, Night vision, Animal recognition, Pan-tilt, Zoom, People recognition
Radio networked	Yes
Radio range	depending on local conditions: 10-30 m

SmartLook Pan & Tilt

Art.-Nr. PPIC52520B

Seite 4 von 4

Technical data - SmartLook Pan & Tilt

Recording modes	Manual / Motion detection
Resolution modes	4K Ultra HD / Full HD (1080p) / VGA (360p)
Sensitivity	-90 dBm
Simultaneous network access	3
Software	App: ABUS App2Cam Plus (Android/iOS)
Storage	Micro-SD
Storage capacity	256
Storage medium	Micro-SD (up to 128GB)
Transmission power	11b: 17 +/- 1,5dBm / 11g: 14 +/- 1,5dBm / 11n: 12,5 +/- 1,5dBm
Vertical angle of view	45 °
Video Content Analysis (VCA)	Human / Animal / Vehicle Detection
Video bitrate	0,256 - 1,5 Mbit/s
Video compression	H.264/ H.264+
Video motion detector included	Yes
WEEE group	09
White balance	AWB
width	160 mm