



The security module is used as additional tamper protection for the ABUS door station or the facial recognition terminal to prevent unauthorised opening of the door in the event of the door station being forced open. It is possible to connect an electric door opener, a motorised lock or an electric locking cylinder (relay max. 2 A @ 30 VDC / 0.5 A @ 125 AC).

Technologies

- Security module for the ABUS Moduvis door station or FaceXess facial recognition terminal
- Tamper protection for the door station or facial recognition terminal
- Interface for electric door openers or motorised locks

Technical data - Security module

Alarm output (NO/NC)	Relay (2 A @ 30 VDC / 0.5A @ 125 VAC)
Application purpose	Entrance area/door intercom
Connectable devices	TVHS20001(S), TVHS20010(S), TVHS21010(S), TVHS30000
Connections	1 x RS-485, 1 x Relay
Current consumption	250 mA
DC power supply	12 – 24 V
Depth	44 mm
Dimensions	(W x H x D) 54 x 44 x 16 mm
Height	16 mm
Housing material	Plastic
Length	44 mm
Max. Air humidity	90 %
Max. Operating temperature	60 °C
Min. operating temperature	-30 °C
Mounting type	Flush socket
Net weight	0.025 kg
PSTI conformity needed	No
Power consumption	3 W

Security module

Art.-Nr. TVHS30330

Seite 2 von 2

Technical data - Security module

Product group	Video door intercom system
Protection class IP	20
WEEE group	05
width	54 mm