

# ABUS Analogue HD/6-Channel Hybrid Video Recorder

Art.-Nr. TVVR33603

Seite 1 von 3



## One for all

The recorder is ideal for hybrid systems, such as simultaneous operation of analogue HD and IP cameras. It also works well for a mixture of new cameras and ones already in place on site. It can be flexibly positioned and stores data exactly as required.

The hybrid video recorder records video data from up to 6 connected cameras - simply integrate a standard 3.5-inch hard disk (accessory) and you're ready to go. Each of the 4 analogue HD channels can be converted into another channel for IP cameras with one click. Also practical: The recorder can be placed wherever it's needed, in a server cabinet or simply next to the monitor from which it is operated. An excellent basis for setting up a flexible and professional surveillance system.

All functions can be accessed via an established user interface - even remotely via the Internet, if desired. Clever modes help to search scenes quickly and efficiently. The powerful data compression ensures efficient memory utilisation. In this way, depending on the configuration, recording can last for weeks or months - e.g. by manual triggering or motion detection. Even start-up is brief: Connect the recorder to the company or home network and access the user interface from a PC and browser or simply connect it to a separate monitor - after a short time, the first live image from the cameras can be seen. Individual settings can also be made quickly.

In the event of operation in the network and a motion alarm, users of the ABUS Link Station app will receive a push notification. The app's Pro version offers unlimited mobile access. Free with Lite version: up to 60 minutes/month data stream (live view/playback).

## Technologies

- Reliably stores video data from up to 4 analogue HD cameras plus 2 IP cameras (2 or up to 8 megapixels); supports simultaneous display of several live streams on one monitor (multi-view)
- Integrate cameras from different manufacturers as needed; also ideal for retrofitting/adding to older systems (supports TVI, AHD, CVI and CVBS); if needed, all 6 channels can be used with IP cameras
- Quickly find the scene you're looking for with clear playback view; stores up to 10 TB on a 3.5 HDD/hard disk (accessory); powerful H.265 Plus video compression for longer recording (depending on camera)
- Lean start-up in just a few minutes directly using a monitor or a PC/browser and the free ABUS IP Installer software (searches the network for IP addresses of connected devices)
- Established user interface for configuration (motion detection, schedules, etc.); alarm as needed via warning tone on the NVR, (on-screen display/OSD signal), e-mail and/or push notification to the app

# ABUS Analogue HD/6-Channel Hybrid Video Recorder

Art.-Nr. TVVR33603

Seite 2 von 3

- Easy integration into a server rack (standard height 1U) by means of a shelf (accessory); place on a flat surface as required, e.g. near the monitor from which users operate the recorder (quiet operation, without fan)
- Practical management for multiple recorders on a central PC via free Central Monitoring Station software (ABUS CMS); up to 256 recorders and 1,024 cameras, if needed in a technology mix (IP, analogue HD)
- Easy mobile access to live stream and recordings with smartphone/tablet via ABUS Link Station app

## Technical data - ABUS Analogue HD/6-Channel Hybrid Video Recorder

|                                   |                                                                                                                              |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Alarm generation                  | Acoustic warning signal, OSD signal, e-mail, App Push                                                                        |
| Article program                   | Performance                                                                                                                  |
| Audio input                       | 1x Cinch (2.0Vp-p, 1KΩ)                                                                                                      |
| Audio output                      | 1x Cinch (Line, 1KΩ)                                                                                                         |
| Battery - GRS type                | CR1220                                                                                                                       |
| Battery - quantity                | 1                                                                                                                            |
| Compatible with ABUS Link Station | Yes                                                                                                                          |
| Compatible with Secoris           | No                                                                                                                           |
| Compatible with Secvest           | No                                                                                                                           |
| Compatible with Smartvest         | No                                                                                                                           |
| Compatible with wAppLoxx          | No                                                                                                                           |
| DC power supply                   | 12 V                                                                                                                         |
| Gross weight                      | 2.9 kg                                                                                                                       |
| Height                            | 48 mm                                                                                                                        |
| Housing                           | 1U Chassis                                                                                                                   |
| Housing material                  | Metal, Plastic                                                                                                               |
| Language OSD                      | DE, UK, FR, NL, DK, IT, PL, ES, SE                                                                                           |
| Length                            | 240 mm                                                                                                                       |
| Max. Air humidity                 | 90 %                                                                                                                         |
| Max. Operating temperature        | 55 °C                                                                                                                        |
| Max. Resolution @ frame rate      | TVI: 5 MPx (2960 x 1665) @ 20 fps ~ 720p @ 25/30fps, AHD/CVI: 5 MPx (2592 x 1944) @ 20 fps ~ 720p @ 25/30fps, CVBS: PAL/NTSC |
| Min. operating temperature        | -10 °C                                                                                                                       |
| Net weight                        | 2.06 kg                                                                                                                      |
| Network connection                | 1x RJ-45 10/100/1000 Mbit/s self-adaptive Ethernet Interface                                                                 |
| Network protocols                 | TCP/IP, DHCP, DNS, DDNS, NTP, SMTP, RTSP, NFS, UPnP™, HTTPS, ABUS Server                                                     |
| PSTI conformity given             | Yes                                                                                                                          |
| PSTI conformity needed            | Yes                                                                                                                          |
| Power                             | 18 W                                                                                                                         |
| Power consumption excl. hard disk | 8                                                                                                                            |

# ABUS Analogue HD/6-Channel Hybrid Video Recorder

Art.-Nr. TVVR33603

Seite 3 von 3

## Technical data - ABUS Analogue HD/6-Channel Hybrid Video Recorder

|                                              |                                                                                                                                     |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Product group                                | Video                                                                                                                               |
| Product security update min until            | 2026-12-31                                                                                                                          |
| Recording modes                              | Manual, time schedule, motion detection, alarm, VCA                                                                                 |
| Resolution HDMI output                       | 1920 × 1080 / 60Hz, 1280 × 1024 / 60Hz, 1280 × 720 / 60Hz, 1024 × 768 / 60Hz                                                        |
| Resolution VGA output                        | 1920 × 1080 / 60Hz, 1280 × 1024 / 60Hz, 1280 × 720 / 60Hz, 1024 × 768 / 60Hz                                                        |
| Resolution recording @ frame rate per camera | 5 MPx @ 20 fps ~ 720p @ 25/30fps                                                                                                    |
| Software                                     | ABUS Link Station App (iOS & Android) / IP Installer                                                                                |
| Storage medium                               | 1x SATA interface (3,5" HDD, max. 10 TB) / NAS                                                                                      |
| Supported IP cameras                         | ABUS IP cameras up to 8 Mpx                                                                                                         |
| Supported browsers                           | Chrome, Edge, IE11 (Plugin)                                                                                                         |
| Synchronized playback                        | 4                                                                                                                                   |
| Total network throughput (input/output)      | 72 MBit/s (24 MBits/48 MBits)                                                                                                       |
| Total video channels                         | 6                                                                                                                                   |
| USB connection                               | 2x USB 2.0                                                                                                                          |
| Video Content Analysis (VCA)                 | Via NVR: 4 channel (TVI) motion detection (person/vehicle) or 2 channel VCA (Intr. Det., Tripwire with person/vehicle), face search |
| Video channels HD-TVI                        | 4                                                                                                                                   |
| Video channels IP                            | 6                                                                                                                                   |
| Video compression                            | H.264 / H.264 Plus / H.265 / H.265 Plus                                                                                             |
| Video input                                  | 4x BNC (1.0Vs-s, 75Ω)                                                                                                               |
| WEEE group                                   | 09                                                                                                                                  |
| width                                        | 315 mm                                                                                                                              |