

# ABUS 5 Megapixel Mini Tube FlexNiteView analog camera

Art.-Nr. TVCC35512

Seite 1 von 2



## Flexible night watchman

This analog 5 megapixel surveillance camera (mini tube design) is suitable for day and night video surveillance. Particularly interesting: Two practical options are available for night vision.

The night vision with this surveillance camera extends up to 30 meters. Either the camera delivers video images in black and white out of the dark, using infrared light that is invisible to humans. The mini tube camera therefore remains discreetly in the background. If desired, it can bring events into clear light using the integrated white light LED.

Individual settings can be made using the compatible ABUS recorder. Particularly practical: a corresponding recorder analyzes the video images specifically and saves them according to your needs (motion detection person/vehicle). Thanks to its design, the compact camera is ideal for discreet surveillance from the wall. It masters backlit situations (outside in sunshine, generally in entrance areas) with ease and even in extremely low light you still get a sharp color image.

## Technologies

- Analog, weatherproof surveillance camera in compact design (approx. 14 cm long), with 5 megapixel image resolution, night vision optionally in black and white or color
- In the dark: use integrated infrared LEDs for black and white image & white light LEDs for color image as required (range up to 30 m, depending on location)
- In low light: low-light function (down to 0.01 lux) & noise reduction (DNR)
- Top wind & weather protection (IP67), viewing angle (105° horizontal, 67° vertical), frame rate (max. 20 fps @ 5 MPx)
- Plug & Play installation (optionally ceiling/wall) incl. 1 x 30 m video combination cable and power supply unit
- Individual settings via compatible recorder from ABUS: e.g. night vision configuration, depending on the recorder

# ABUS 5 Megapixel Mini Tube FlexNiteView analog camera

Art.-Nr. TVCC35512

Seite 2 von 2

also object detection (person/vehicle) + Access on the move via ABUS Link Station app

- Supports TVI, AHD, CVI and FBAS/CVBS formats

## Technical data - ABUS 5 Megapixel Mini Tube FlexNiteView analog camera

|                              |                                                     |
|------------------------------|-----------------------------------------------------|
| Aperture                     | F2.0                                                |
| Application purpose          | General surveillance                                |
| Article program              | Performance                                         |
| Colour                       | Other                                               |
| Construction type of device  | Tube                                                |
| DC power supply              | 12 (+/-25 %) V                                      |
| Depth                        | 139 mm                                              |
| Dimensions                   | (LxBxH) 139x61x58 mm                                |
| Gross weight                 | 0.8 kg                                              |
| Height                       | 58 mm                                               |
| Horizontal viewing angle     | 105 °                                               |
| Housing material             | Metal                                               |
| IR LEDs                      | Yes                                                 |
| IR range (up to)             | 30 m                                                |
| Image optimization           | BLC / HLC / DWDR                                    |
| Image sensor                 | CMOS                                                |
| Max. Air humidity            | 90 %                                                |
| Max. Operating temperature   | 60 °C                                               |
| Max. Resolution @ frame rate | TVI / AHD / CVI: 2960 x 1665 @ 20 fps, CVBS: PAL    |
| Microphone                   | Yes                                                 |
| Min. operating temperature   | -40 °C                                              |
| Minimum illumination (IR)    | 0 lx                                                |
| Minimum illumination (color) | 0.01 lx                                             |
| Net weight                   | 0.29 kg                                             |
| Power consumption            | 3.3 W                                               |
| Product group                | Video                                               |
| Protection class IP          | 67                                                  |
| Resolution                   | 5 MP                                                |
| Resolution modes             | TVI: 5 MPx @ 20 fps, 4 MPx @ 25 fps, 1080p @ 25 fps |
| Video output                 | 1x BNC                                              |
| WEEE group                   | 09                                                  |
| White light LEDs             | 1 St.                                               |
| width                        | 61 mm                                               |