



THE NARROW SOLUTION

Narrow door constructions can be reliably secured with this additional lock.

Even with narrow assembly conditions, you should not have to compromise on the security of your front doors. This additional lock is suitable for doors in particularly narrow assembly conditions with rebate thicknesses from 0 to 29 millimetres and door thicknesses from 38 to 90 millimetres. It secures the locking side with heavy-duty dowels and with a strong oval bolt made of solid steel. The rotary knob on the inside ensures a quick escape route. The ABUS Pfaffenhain rim cylinder V356 ensures secure locking using one of the three keys supplied. The cylinder can be optionally protected by a PZS 80 armoured plate.

Technologies

- Solid extra narrow construction
- Solid wall anchor: concealed fastening
- Backset: 45 mm
- Heavy duty double locking deadbolt: locks with two turns of the key
- With external cylinder ABUS Pfaffenhain
- Optional accessories: PZS 80 armoured plate to optimally protect the door cylinder
- Incl. three keys

Operation and use

- Rim Lock for entrance doors with narrow frames
- For rebates between 0 - 29 mm and door thicknesses between 38 - 90 mm
- Operated with a key on the outside and with a thumbturn on the inside
- For entrance doors to secure the locking side (Tip: protect the hinged side additionally!)
- Available keyed alike with ABUS padlocks and door cylinders

Variants

7510 white



Security Tech Germany

Seite 2 von 2

-
- Finishes: brown, white, stainless steel look
-

Technical data - 7510 white

Security Level Home Security	9
Weight	1113 g
alarm function	No
colour	white
door guard	No
type of cylinder	Exterior cylinder
EAN	4003318082139