

Motion detector PIR MW (PET)

Art.-Nr. AZBW10121

Seite 1 von 3



PLAY IT SAFE: CLEARLY DETECT UNAUTHORIZED PERSONS

Close monitoring: 2 sensors, twice as safe

The EN Grade 2 certified wire motion detector combines the advantages of two sensors and provides high security against false alarms: An alarm is only if both sensors with separate detection methods, passive infrared (PIR) and microwaves (MW), detect a movement. For example, the PIR sensor reacts to moving body heat, while the MW sensor actively monitors the surroundings (cf. radar).

PET immunity: For your beloved pet

Optional pet-immune" function, adjustable to 3 levels, distinguishes between humans and animals. Moving persons are reliably detected while pets weighing up to 15 kg are ignored. In rare individual cases, however, a lighter animal may set off the detector, e.g., if it runs, jumps, or flies close to the detector.

Technology and installation

Optimal mounting location is in a corner, about 1.80 to 2.40 m above the floor. The expected direction of travel of an intruder should be across the detector. The viewing angle is approx. 90 degrees, the detection range (depending on the mounting height) up to 12 x 12 m. The spherical lens design ensures extremely reliable detection thanks to uniform room coverage. Thanks to integrated anti-creep protection, the detector has no blind spots and also detects people directly underneath it.

Individual range settings

The microwave range is variably adjustable to cover exactly the desired area.

Technologies

- Passive infrared motion detector (PIR) with microwave element (MW) for indoor use

Motion detector PIR MW (PET)

Art.-Nr. AZBW10121

Seite 2 von 3

- Dual detector: PIR sensor and MW sensor combined in one detector
- Preventive protection against false alarms thanks to twofold detection
- Pet-immune optional: Ignores animals up to approx. 15 kg
- Monitors entire rooms (detection area approx. 12 x 12 m)
- High security: No blind spots thanks to anti-creep protection
- EN Grade 2 Certification

Technical data - Motion detector PIR MW (PET)

Adjustable sensitivity	Yes
Alarm memory	Yes
Animal immune	Yes, < 30 kg
Areas of application	Interior
Certifications	EN 50131 Grad 2, VSÖ GS-N
Compatible with	Secoris, Secvest, Terxon
Cover monitoring	No
Creep protection	Yes
Current consumption	17 mA
DC power supply	9-16 V
Depth	46 mm
Detection area detector (m)	12 m
Detection method	Heat detection, Microwave
Detection speed	0,3-2 m/s
Dimensions	(WxHxD) 66x104x46 mm
Display type	Yes
EN	Level 2
Height	104 mm
Housing material	Plastic
Length	46 mm
Max. Air humidity	90 %
Max. Detection area (indoor)	55 m
Max. Operating temperature	45.5 °C
Min. humidity	10
Min. operating temperature	-10 °C
Mounting location	Wall
Net weight	0.099 kg
PIR viewing angle	85.9 °
Product group	Detectors
Radio frequency	24,200 MHz
Sensor type	PIR, microwave

Motion detector PIR MW (PET)

Art.-Nr. AZBW10121

Seite 3 von 3

Technical data - Motion detector PIR MW (PET)

Status display	Yes
Tamper monitoring	Yes
Type of protection	Intrusion protection
VdS class	without
WEEE group	09
width	66 mm