

# 10 m Preassembled BNC Cable

Art.-Nr. TVAC40040

Seite 1 von 2



For optimum connection of video components

The pre-assembled coaxial cable establishes the connection between video components, e.g. from the camera to the recorder. The cable has a resistance of 75 ohms and a BNC connector at both ends.

Precisely fitting length

The pre-assembled BNC cable is available in lengths of 20 m (TVAC40050), 10 m (TVAC40040), 5 m (TVAC40030), 3 m (TVAC40020), 2 m (TVAC40010) and 1 m (TVAC40000).

## Technologies

- For connecting analogue cameras to hard disk recorders or monitors
- High signal shielding

## Technical data - 10 m Preassembled BNC Cable

|                            |                         |
|----------------------------|-------------------------|
| Application purpose        | indoors                 |
| Attenuation                | 0.32 dB                 |
| Cable length               | 10 m                    |
| Colour                     | black                   |
| Connections                | BNC (male) – BNC (male) |
| Diameter                   | 5 mm                    |
| Housing material           | PVC                     |
| Impedance                  | 75 Ω                    |
| Insulation                 | PE                      |
| Insulation resistance      | 5,000 MΩ                |
| Max. Operating temperature | 60 °C                   |
| Min. operating temperature | -10 °C                  |
| Net weight                 | 0.368 kg                |
| Outside diameter           | 50 mm                   |
| PSTI conformity needed     | No                      |

# 10 m Preassembled BNC Cable

Art.-Nr. TVAC40040

Seite 2 von 2

---

## Technical data - 10 m Preassembled BNC Cable

|               |             |
|---------------|-------------|
| Product group | Accessories |
|---------------|-------------|