

Secvest Touch Wireless Alarm System

Art.-Nr. FUAA50500

Seite 1 von 4



THE MULTI-TALENT: ROBUST PROTECTION IN A STYLISH DESIGN

Protection against break-ins, fire, water and emergencies, unique active intrusion protection and much more: Whether for the home, office or business - in the first-class design of the Secvest Touch alarm panel.

Proven all-round security

With a wide range of wireless components (48 per system), mechatronic detectors and optional wired detectors. Operation, such as arming and disarming, is very convenient thanks to the elegant touchscreen interface. The capacitive user interface lights up permanently or when touched - and is always easy to read thanks to the brightness sensor. A special cleaning mode is used to safely clean the cover. Operation is possible by wireless door cylinder, code input, proximity chip key or remote control. For maximum security and convenience for up to 50 users.

The decisive step ahead

The free Secvest app (smartphone, tablet) makes operation and status queries very easy. Electronic wireless door cylinders can be released and locked directly. Live images and recordings from max. 6 IP cameras are visible in the app, even when you are on the move.

Active intrusion protection with 2-fold security

Mechatronic detectors fitted to windows and doors already recognise the first attempt to break in - before the perpetrator gets into the house. Robust mechanism cleverly integrated.

Presence simulation and building automation: Wireless sockets and switching outputs are used to control lights, external window blinds, hi-fi, etc.

Technologies

- Proven all-round security in a new, elegant design

Secvest Touch Wireless Alarm System

Art.-Nr. FUAA50500

Seite 2 von 4

- Convenient operation via app (Android/iOS), web browser, at the alarm panel and with many freely selectable control options such as remote control, chip key or code input
- Active intrusion protection due to the combination with additional mechatronic wireless window locks/door deadlocks
- Up to 48 individually identifiable wireless detectors, 4 wired detectors, 8 control panels, 50 remote controls
- Possible connection to control centres via control centre protocols, integrated dialler
- VdS Home certified and EN 50131-1 Level 2

Technical data - Secvest Touch Wireless Alarm System

AC power supply	230 V
Access protection	Yes
Active intrusion protection	With mechatronic components (permanent monitoring)
Battery type	7,4V 2500mAh 18,5Wh (FUBT50000)
Certifications	VdS Home, EN 50131 Grad 2
Colour	white, white
Communication/ Alarm	Monitoring station, voice, SMS, email, push notification
Connections	230 V AC / 13,8 V DC screw terminal, a/b screw terminal, siren connection, 2-4 wired zones, 2 outputs
DC power supply	13,8 V
Depth	46 mm
Dimensions	(WxHxD) 205x285x46 mm
Display type	Display
Duplex antenna technology	Yes
EN	Level 2
Emergency power supply	Yes
Environmental class	II
Event memory	Yes
Expandable (hybrid)	No
Expandable (radio)	Yes
External interface	Yes
Height	285 mm
Housing material	ABS
Integrated siren	Yes
Language Manual	DE, EN, FR, NL, DK, IT
Language OSD	DE, EN, FR, NL, DK, IT, ES, SE, PL, RU
Length	46 mm
Max. Emergency power runtime	24 h
Max. Max. number of detector groups	52

Secvest Touch Wireless Alarm System

Art.-Nr. FUAA50500

Seite 3 von 4

Technical data - Secvest Touch Wireless Alarm System

Max. Number of control units	8
Max. Operating temperature	40 °C
Max. Receive range (building)	30 m
Max. Receive range (free field)	100 m
Max. Transmit range (free field)	100 m
Max. Transmitting range (building)	30 m
Mechanical protection	No
Menu navigation	Voice-activated
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Ambient conditions adapted to optimal transmission power
Net weight	1.24 kg
Network connection	Ethernet
Network protocols	HTTPS
Number of events	600
Number of operating elements	8
Number of remote controls	50
Number of sabotage detector groups	52
Number of users	50
Number of virtual IP zones	6
Number of wire zones	2 x CC or 4 x FSL
Number of wireless zones	48
Operating mode	Panel: via Secvest key, wireless remote control, extra wireless door lock, proximity chip key, wireless key switch and wireless control panel / Wireless: via web server, mobile application, telephone
Outputs	32 wireless, 4 wired
PSTI conformity given	No
PSTI conformity needed	Yes
Power supply unit	Integrated or external
Product group	Alarm panel
Programming 1	Directly at the alarm control panel or via web server
Protocols	NSL: Fast format, contact ID, SIA (analogue and IP); maintenance: Scancom, Scanfast, Tunstall
Radio alarm bandwidth	Narrow band
Radio frequency	868.6625 MHz

Secvest Touch Wireless Alarm System



Security Tech Germany

Art.-Nr. FUAA50500

Seite 4 von 4

Technical data - Secvest Touch Wireless Alarm System

Radio networked	Yes
Radio power	10 mW
Remote maintenance	Yes
Security gradient	2
Software version	3.01.31
Sub-areas/monitoring areas	4
Switching outputs	4
Tamper monitoring	Yes
VdS class	Other
Video verification	Yes, in connection with e.g. TVIP41550, IPCB42500, IPCB42501, IPCB62500, IPCB72500, IPCB72501
Voltage monitoring	Yes
WEEE group	09
standard	EN50131-1 Grad 2
width	205 mm