

Smartvest Wireless Button

Art.-Nr. FUBE35020A

Seite 1 von 2



The Smartvest Wireless Button lets you control various Smartvest Wireless Alarm System actuators, such as the Wireless Socket, the Wireless Door Bell or even self-configured scenarios, within the system. The Wireless Button can be mounted using the click-mount for walls supplied, so that the button can be easily removed for mobile use. Alternatively it can be mounted using adhesive mounting. Two different actions can be triggered by assigning the action a short or long press. If the battery is low, this is transmitted to the alarm panel.

Technologies

- Smartvest extension for controlling Smartvest actuators, i.e. Wireless Socket, Wireless Door Bell or self-configured scenarios
- Comes with a click-mount for walls, from which the button can be easily removed for mobile use. Alternatively it can be mounted using adhesive mounting.
- Individual configuration is possible for two actions (short/long press)
- Visual feedback via orange LED when starting up and in use
- Low battery notification sent to the Smartvest alarm control panel

Technical data - Smartvest Wireless Button

Battery - battery operation	Yes
Battery - max. battery life	1.5 years(s)
Battery - quantity	1
Battery type	CR2032 (3V)
Colour	White
Compatible with Secvest	No
Compatible with Smartvest	Yes
Current consumption	0.014 mA
Current consumption standby	0.0086 mA

Smartvest Wireless Button

Art.-Nr. FUBE35020A

Seite 2 von 2

Technical data - Smartvest Wireless Button

Depth	17 mm
Dimensions	(B x L x H) 30 x 17 x 70 mm
Display type	LED
Gross weight	0.058 kg
Height	70 mm
Housing material	Plastic
Max. Air humidity	80 %
Max. Operating temperature	40 °C
Min. humidity	10
Min. operating temperature	-10 °C
Net weight	0.028 kg
PSTI conformity given	No
PSTI conformity needed	Yes
Product group	Detectors
Radio frequency	868 MHz
Radio modulation	FSK
Radio range	(Depending on installation) 30 - 100 m
Tamper protection	No
Transmission power	4,5 dBm
WEEE group	09
width	30 mm