

# 23.8" Full HD LED Monitor

Art.-Nr. TVAC10061

Seite 1 von 3



## Detailed surveillance images in full HD

The convenient LED monitor with a 24" (inch) display size shows you detailed surveillance images in 16:9 format and in full HD 1080p resolution.

## Full HD monitor for easy identification

Thanks to a rapid reaction time (of just 5ms), the LED monitor displays you surveillance pictures almost in real time. It shows quick movements on the screen clearly and continuously, without any distortions, flickering or ghost images. You'll see accurately detailed images in full HD quality so you can monitor, easily identify individuals and quickly resolve situations.

## Connections for a wide range of applications

Connect the monitor to a recorder or PC with flexible options. Thanks to the HDMI input, the monitor is optimally suited to displaying images in full HD. An additional VGA input secures the connection to a variety of surveillance systems, a computer and other components.

## Energy efficiency for long-term monitoring

The efficient LED display ensures very low power consumption - ideal for long-term use.

## Simple installation with VESA brackets

The monitor is compatible with standard VESA brackets for quick installation on the wall or ceiling.

Tip: The monitor is also available in 21.5 with full HD resolution (TVAC10033) and in 27 with 4K resolution (TVAC10071).

## Technologies

# 23.8" Full HD LED Monitor

Art.-Nr. TVAC10061

Seite 2 von 3

- 24 LED monitor with full HD resolution: 1920 x 1080 pixels
- Fast reaction time (5 ms) for flowing images
- Brilliant colour display and high contrast in 16:9 format
- Ideal for high-resolution full HD recording systems
- Graphical on-screen display (OSD)
- Connections: HDMI, VGA
- Low power consumption for long-term monitoring (LED technology)
- Compatible with VESA brackets for wall and ceiling installation

## Technical data - 23.8" Full HD LED Monitor

|                                      |                    |
|--------------------------------------|--------------------|
| AC power supply                      | 100~240 V          |
| Brightness                           | 250                |
| Color levels                         | 16.7               |
| Colour                               | black              |
| Comb filter                          | 3D                 |
| Connections                          | 1 x HDMI, 1 x VGA  |
| Contrast ratio                       | 1000:1             |
| Depth                                | 227 mm             |
| Dimensions                           | 540 x 418 x 227 mm |
| Display surface                      | matte              |
| Gross weight                         | 4.44 kg            |
| Height                               | 418 mm             |
| Housing material                     | Plastic            |
| Image format                         | 16:9               |
| Input                                | 1 x HDMI, 1 x VGA  |
| Length                               | 227 mm             |
| Max. Air humidity                    | 90 %               |
| Max. Operating temperature           | 60 °C              |
| Max. number of video feeds           | 2                  |
| Min. operating temperature           | -20 °C             |
| Monitor type                         | LED                |
| Net weight                           | 3.45 kg            |
| PSTI conformity needed               | No                 |
| Power consumption                    | 30 W               |
| Product group                        | Accessories        |
| Response time                        | 14 ms              |
| Screen diagonal                      | 23.8 in            |
| Signal detection                     | Automatic          |
| Viewing angle<br>horizontal/vertical | 178° x 178°        |

# 23.8" Full HD LED Monitor



Security Tech Germany

Art.-Nr. TVAC10061

Seite 3 von 3

---

## Technical data - 23.8" Full HD LED Monitor

|            |        |
|------------|--------|
| WEEE group | 09     |
| width      | 540 mm |