

# 93RK/110 Oval cylinder without cylinder

Seite 1 von 2



## HIGH SECURITY

Want to secure a cash machine or roller shutter, but the spot is hard to reach?

Or want to secure high value assets and expensive objects? Our 93RK Monobloc padlock can do the job. Shackle and lock body are made of hardened special steel with Nano Protect™ coating. This makes the padlock extremely secure.

## Technologies

- Shackle and lock body made of hardened special steel with NANO PROTECT™ coating for extra corrosion resistance
- Protected against drilling or pulling open
- Cylinder can be replaced and re-keyed to match an existing key
- 0: Accepts standard oval cylinders
- EPZ: Accepts standard Euro profile half cylinders (Length: 10/30)
- fig. 8: Accepts all cylinders from the ABUS 83 series
- SSF Kl. 5/ CEN Kl. 6
- Key retaining: key is needed for locking (lock retains key until locked)

## Operation and use

- To secure assets and objects of greater value or those at a high risk of theft
- For the highest security requirements
- For securing warehouses, factory gates, containers and lorries etc.

## Technical data - 93RK/110 Oval cylinder without cylinder

|                              |         |
|------------------------------|---------|
| Depth e                      | 29 mm   |
| Height f                     | 70 mm   |
| Horizontal clearance b       | 34,5 mm |
| Keyed alike                  | No      |
| Locking type                 | key     |
| Security Level Home Security | 10      |

# 93RK/110 Oval cylinder without cylinder

Seite 2 von 2

## Technical data - 93RK/110 Oval cylinder without cylinder

|                      |                  |
|----------------------|------------------|
| Security card        | No               |
| Shackle diameter d   | 15 mm            |
| Vertical clearance c | 21,5 mm          |
| Weight               | 1202 g           |
| Width a              | 110 mm           |
| colour               | silver           |
| type of cylinder     | without cylinder |
| EAN                  | 4003318889943    |

## Technical drawing

