



DIGITAL, RADIO-NETWORKED LOCKING TECHNOLOGY FOR 160 DOORS

The electronic locking system for real-time access management in commercial properties and public facilities. The Control unit manages the radio networked wAppLoxx Pro Plus system including all door cylinders, other components, and the app. The integrated software is included free of charge. It can be operated online (remote access) or via LAN, data transmission is always encrypted and made via a secure connection.

Extensive, flexible, well organized

One control integrates up to 32 door components and 6 radio repeaters into one system. Need more? Just combine up to 5 control units and scale up to 160 doors (1:4 cascading). The software's transparent locking plan matrix manages 1,000 users in 160 door groups and 100 user groups.

Efficient software management and app operation

Complex building access requirements are conveniently set up in the intuitive software. Locking rights and operations are controlled, changed, and monitored directly here - all changes are applied at the push of a button (high-performance real-time management). The system is designed for the integration of 2 alarm systems (EMA) for de-/activation directly at the door and for 10 IP cameras for access verification via video image. Popular feature: The app turns any smartphone into a locking medium.

This makes wAppLoxx Pro Plus the perfect locking system for companies and the public sector.

Technologies

- Central control unit of the wirelessly-networked wAppLoxx Pro Plus system (compatible with WLX Pro cylinders and WLX cylinders, depending on the version)
- Integrated software for programming and managing the key system for up to 1,000 users (wAppLoxx Pro Plus Manager)
- Possible operating modes: offline, local network and online with internet connection
- Up to 32 wireless door components can be integrated for each WLX Pro Control Plus and with a maximum of 6 WLX

WLX Pro Control Plus

Art.-Nr. ACC016000

Seite 2 von 3

Pro Repeaters each

- Scaling up the system by combining up to 5 control units to a total of 160 WLX Pro door components
- Assignment of locking authorisations in the key plan matrix for up to 160 door groups and 100 user groups
- Flexible access release – even when on the move – for all wAppLoxx Pro door components via iOS/Android app (subject to a charge)
- Control of up to 2 intruder alarm systems or 2 security zones directly at the door (inevitability protection against false alarms) and integration of up to 10 ABUS IP cameras for access verification (live image in the app)
- Intelligent event control (e.g. email sent in the event of an invalid access attempt)
- Automatic provision of software updates

Technical data - WLX Pro Control Plus

Article abbreviation	WLX-PP-CTRL
Closing media	1000
Colour	white
Compatible with	WLX Pro
Connections	Relay 1-4: 30 V DC / 2A max. - Inputs 1-6: 0V/12V / 0.1A max.
Current consumption	500 mA
DC power supply	1,5 A / 12 V
Depth	53 mm
Dimensions	277 × 247 × 53 mm
Encryption	AES 128-bit
Environmental conditions	max. 80% relative humidity, non-condensing
Height	247 mm
Housing material	Plastic
Length	53 mm
Max. operating temperature	40 °C
Min. operating temperature	0 °C
Mounting type	Surface mounted
Net weight	0.996 kg
PSTI conformity given	Yes
PSTI conformity needed	Yes
Product security update min until	2030-12-31
Protocol and time function	Yes
Radio frequency	868.3 MHz
Radio functions	Permissions can be selected for access and/or arm/disarm, special keys for security services, remote access authorisation, remote arm/disarm, event control and email notification, log and time function, camera integration
Radio range	up to 30 m indoors / free field nominal 100 m

WLX Pro Control Plus



Security Tech Germany

Art.-Nr. ACC016000

Seite 3 von 3

Technical data - WLX Pro Control Plus

VdS class	without
signaling	Status LEDs
width	277 mm