ABUS EasyLook Monitor

Art.-Nr. PPDF17000M

Technical data - ABUS EasyLook Monitor

Alarm generation	Acoustic warning signal
Article program	Comfort
Battery - battery operation	Yes
Battery - permanently installed	Yes
Battery - quantity	2
Battery - runtime	Up to 2 h
Battery type	5200mAH rechargeable Battery
Channel width	20/40 MHz
Colour	Black
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Connections	Power: DC plug / USB 2.0
DC power supply	12 V
Dimensions	(W x L x H) 199 x 32 x 123 mm
Encryption	WPA2
Frequency range	2,403 - 2,478 GHz
Housing material	Plastic
Language OSD	DE, GB, FR, NL, DK, IT
Loudspeaker	Yes
Max. Operating temperature	40 °C
Microphone	Yes
Min. operating temperature	0 °C
Modulation	DSSS , OFDM
Monitor type	7" Capacitive Touchscreen
Number of channels	4
Plug type	DC-plug: 5,5 x 2,1 mm
Power consumption	8.4 W
Radio range	(Depending on installation) 20 - 50 m
Recording modes	Schedule, motion detection
Resolution	1024 x 600p
Resolution modes	3 MP (2304 x 1296)
Resolution recording @ frame rate per camera	3MP @15 fps
Screen diagonal	7 in
Sensitivity	-88 dBm
Storage medium	MicroSD Class 10 (max. 128GB)

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 09/2026

ABUS EasyLook Monitor

Technical data - ABUS EasyLook Monitor

Transmission channels	13
Transmission power	20 dBm
Video compression	H.264+
Views	1 / 4 (Quad)

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 09/2026