

Additional camera for ABUS EasyLook BasicSet

Art.-Nr. PPDF17520

Seite 1 von 3



Up to 4 cameras per monitor

Add up to 4 cameras to your ABUS EasyLook BasicSet. Commissioning an additional camera is just as easy as with the basic set and done in just a few steps.

Just like the camera in the basic set, an additional camera reliably delivers video images day & night. The camera performs its job without internet/Wi-Fi, without an app and without a smartphone - all it needs is power. The video data and settings are securely encrypted and quickly transmitted wirelessly between the camera and the monitor of the basic set.

Commissioning the additional camera is just as easy as with the basic set. A total of up to 4 cameras can be easily operated with one monitor; if needed, the screen displays all live images from the cameras simultaneously - with a simple finger gesture, it is possible to quickly switch between the "quad view" and individual camera images.

So you always have a view of what is happening in your shop or around your home, whether at the entrance, in front of the garage, on the terrace or in the garden.

Technologies

- Extension for the ABUS EasyLook BasicSet; additional camera with high wireless range, reliable motion detection, intercom function, night vision, privacy zone masking and much more
- A total of 4 security cameras can be wirelessly connected to the monitor of the ABUS EasyLook BasicSet
- Very easy to use, even for subsequent commissioning; supply power to the additional camera, add it to the set monitor and the first live image will appear
- Inside and outside, the surveillance camera reliably detects people/animals thanks to its clever motion detection (integrated motion detector/passive infrared sensor, PIR for short, detects heat; camera software analyses for motion in parallel)
- Monitor immediately and automatically switches to alarm and recording mode (siren sound on the monitor can be

Additional camera for ABUS EasyLook BasicSet

Art.-Nr. PPDF17520

Seite 2 von 3

switched on/off as required; insert standard microSD card with up to 128 GB for storage)

- Personal settings via monitor; deactivate audio/sound for recordings (GDPR/data protection compliant), image areas with/without recognition, schedules, privacy zones
- Clear night vision in black and white (via infrared LED) up to 15 metres, 3-megapixel camera resolution, zoom function, 82-degree viewing angle, camera protection class IP66 (weatherproof; protection against strong jets of water, dustproof)
- No further costs (no subscription, no cloud)

Technical data - Additional camera for ABUS EasyLook BasicSet

Article program	Comfort
Base event	PIR & Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Controllable with app	No
DC power supply	12 V
Day/night switching	Auto
Depth	161 mm
Dimensions	(W x L x H) 61 x 161 x 77 mm
Encryption	WPA2
Focal length	4 mm
Frequency range	2,403 - 2,478 GHz
Height	77 mm
Horizontal viewing angle	82 °
Housing material	Plastic
IR LEDs	Yes
IR range (up to)	15 m
IR swivel filter	Yes
Image sensor	1/3" CMOS
Location	Outdoor use
Loudspeaker	Yes
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Max. Resolution @ frame rate	2305 x 1296 @15fps
Microphone	Yes
Min. humidity	30

Additional camera for ABUS EasyLook BasicSet

Art.-Nr. PPDF17520

Seite 3 von 3

Technical data - Additional camera for ABUS EasyLook BasicSet

Min. operating temperature	-10 °C
Minimum illumination (IR)	0.1 lx
Minimum illumination (color)	1 lx
Net weight	0.41 kg
Optical wavelength	940
PIR range	8 m
PIR viewing angle	85 °
PSTI conformity needed	No
Plug type	DC-plug: 5,5 x 2,1 mm
Power consumption	3.6 W
Power supply	Power adapter
Privacy zones	4
Protection class IP	66
Radio functions	People recognition, Intercom (2-way audio), Zoom, Night vision
Radio networked	Yes
Radio range	(Depending on installation) 20 - 50 m
Resolution modes	2305 x 1296 (3MP)
Sensitivity	-88 dBm
Transmission power	20 dBm
Vertical angle of view	42 °
Video bitrate	2Mbps
Video compression	H.264+
Video motion detector included	Yes
Video system	Stand-alone
WEEE group	09
White balance	Auto
width	61 mm