

ABUS Analogue HD/8-Channel Hybrid Video Recorder

Art.-Nr. TVVR33802

Seite 1 von 3



One for all

The recorder is ideal for hybrid systems, such as simultaneous operation of analogue HD and IP cameras. It also works well for a mixture of new cameras and ones already in place on site. It can be flexibly positioned and stores data exactly as required.

The hybrid video recorder records video data from up to 8 connected cameras - simply integrate a standard 3.5-inch hard disk (accessory) and you're ready to go. Each of the 4 analogue HD channels can be converted into another channel for IP cameras with one click. Also practical: The recorder can be placed wherever it's needed, in a server cabinet or simply next to the monitor from which it is operated. An excellent basis for setting up a flexible and professional surveillance system.

All functions can be accessed via an established user interface - even remotely via the Internet, if desired. Clever modes help to search scenes quickly and efficiently. The powerful data compression ensures efficient memory utilisation. In this way, depending on the configuration, recording can last for weeks or months - e.g. by manual triggering or motion detection. Even start-up is brief: Connect the recorder to the company or home network and access the user interface from a PC and browser or simply connect it to a separate monitor - after a short time, the first live image from the cameras can be seen. Individual settings can also be made quickly.

In the event of operation in the network and a motion alarm, users of the ABUS Link Station app will receive a push notification. The app's Pro version offers unlimited mobile access. Free with Lite version: up to 60 minutes/month data stream (live view/playback).

Technologies

- Reliably stores video data from up to 4 analogue HD cameras plus 4 IP cameras (2 or up to 8 megapixels); supports simultaneous display of several live streams on one monitor (multi-view)
- Integrate cameras from different manufacturers as needed; also ideal for retrofitting/adding to older systems (supports TVI, AHD, CVI and CVBS); if needed, all 8 channels can be used with IP cameras
- Quickly find the scene you're looking for with clear playback view; stores up to 10 TB on a 3.5 HDD/hard disk (accessory); powerful H.265 Plus video compression for longer recording (depending on camera)
- Lean start-up in just a few minutes directly using a monitor or a PC/browser and the free ABUS IP Installer software (searches the network for IP addresses of connected devices)
- Established user interface for configuration (motion detection, schedules, etc.); alarm as needed via warning tone on the NVR, (on-screen display/OSD signal), e-mail and/or push notification to the app

ABUS Analogue HD/8-Channel Hybrid Video Recorder

Art.-Nr. TVVR33802

Seite 2 von 3

- Easy integration into a server rack (standard height 1U) by means of a shelf (accessory); place on a flat surface as required, e.g. near the monitor from which users operate the recorder (quiet operation, without fan)
- Practical management for multiple recorders on a central PC via free Central Monitoring Station software (ABUS CMS); up to 256 recorders and 1,024 cameras, if needed in a technology mix (IP, analogue HD)
- Easy mobile access to live stream and recordings with smartphone/tablet via ABUS Link Station app

Technical data - ABUS Analogue HD/8-Channel Hybrid Video Recorder

Alarm generation	Acoustic warning signal, OSD signal, e-mail
Article program	Performance
Audio input	1x RCA (2.0Vp-p, 1kΩ)
Audio output	1x RCA (Linear, 1kΩ)
Battery - quantity	1
Compatible with ABUS Link Station	Yes
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Construction type of device	Other
DC power supply	12 V
Decoding performance (local live view & playback)	4x 2MPx
Depth	240 mm
Dimensions	(W x L x H) 315 x 240 x 48 mm
Gross weight	2.9 kg
Height	48 mm
Housing	1U Chassis
Housing material	Metal, Plastic
Language OSD	DE, UK, FR, NL, DK, IT, PL, ES, SE
Max. Air humidity	90 %
Max. Operating temperature	55 °C
Max. Resolution @ frame rate	TVI: 8 MPx, 5MPx, 4MPx, 3MPx, 2MPx @ 30fps / 1MPx @ 60 fps AHD: 5MPx, 4MPx, 2MPx, 1MPx @ 30fpsCVI: 4MPx, 2MPx, 1MPx @ 30fpsCVBS: Support
Max. number of video feeds	8
Min. operating temperature	-10 °C
Net weight	2.072 kg
Network connection	1x RJ-45 10/100 Mbit/s self-adaptive Ethernet interface
Network protocols	TCP/IP, DHCP, DNS, DDNS, NTP, SMTP, RTSP, NFS, UPnP™, HTTPS, ABUS Server
PSTI conformity given	Yes
PSTI conformity needed	Yes

ABUS Analogue HD/8-Channel Hybrid Video Recorder

Art.-Nr. TVVR33802

Seite 3 von 3

Technical data - ABUS Analogue HD/8-Channel Hybrid Video Recorder

Power	21 W
Power consumption	21 W
Power consumption excl. hard disk	15
Product group	Video
Recording modes	Manual, time schedule, motion detection
Resolution HDMI output	1920 × 1080 / 60Hz, 1280 × 1024 / 60Hz, 1280 × 720 / 60Hz, 1024 × 768 / 60Hz
Resolution VGA output	1920 × 1080 / 60Hz, 1280 × 1024 / 60Hz, 1280 × 720 / 60Hz, 1024 × 768 / 60Hz
Resolution recording @ frame rate per camera	8MPx @ 8 fps / 5MPx @ 12fps / 4MPx @ 15 fps / 3 MPx @ 18 fps / 2MPx, 1MPx, WD1, 4CIF, VGA, CIF @ 30 fps
Software	ABUS Link Station (iOS & Android) / ABUS CMS / IP Installer
Storage medium	1x Sata interface (3,5" HDD, max. 10 TB) / NAS
Supported IP cameras	see compatibility list
Supported browsers	IE11 (Plugin), Edge/Chrome (Plugin)
Synchronized playback	4
Total network throughput (input/output)	72 Mbit/s
Total video channels	8
USB connection	2x USB 2.0
Video channels HD-TVI	4
Video channels IP	8
Video compression	H.264 / H.264 Plus / H.265 / H.265 Plus
Video input	4x BNC (1.0Vp-p, 75Ω)
Video motion detector included	Yes
WEEE group	09
width	315 mm