

IP Mini Tube 4 MPx Black (2.8mm, WL)

Art.-Nr. IPCS34611A

Seite 1 von 4



SMALL CAMERA, BIG DETAILS AT NIGHT

This IP Mini Tube is a compact LAN camera with full colour day/night function and delivers images in 4 MPx resolution. With its white-light LEDs in IP67 housing, it is designed for indoor/outdoor use by day and night. Mobile access to the camera via ABUS Link Station app.

Discreet surveillance: strong in the dark

Clear colour images in total darkness thanks to full colour tag/night technology - rich in detail for solid evidence. The slightest residual light is effectively amplified by the special lens and the extra light-sensitive image sensor. The white-light LEDs provide precisely regulated extra light for the image sensor, barely visible to the eye.

2 variants for maximum flexibility

The camera is available with 2 focal lengths: 2.8 mm / 108° field of view (IPCS34511A) and 4 mm / 95° (IPCS34511B).

Automatic object detection

The security camera distinguishes relevant movements (people, vehicles) from disturbing influences (branches, light, etc.) and minimises unnecessary motion alarms.

Recording and compatibility

Recording takes place on ABUS NVR, VMS or microSD card. The camera is compatible with ABUS Secvest, Secoris and WLX Pro.

Quick start-up

Mounting with protected cable via installation box (TVAC32600). The ABUS IP Installer software makes network setup easier.

IP Mini Tube 4 MPx Black (2.8mm, WL)

Art.-Nr. IPCS34611A

Seite 2 von 4

Notes: Without power supply unit, because power is supplied by PoE.
The effective LED range varies depending on the location.

Technologies

- 4 MPx resolution (2,688 x 1,520 @ 25 fps) for crisp surveillance images
- 2.8 mm fixed lens for longer distances (108° angle of view)
- Detailed, highly usable colour images in the dark thanks to full-colour day/night technology; effectively amplifies even minimal ambient light using a special lens and highly light-sensitive image sensor
- Discreet illumination of the field of view with white-light LEDs (up to 30 m range) for accurate colour images in total darkness (e.g. indoors); finely metered lighting for the light-sensitive image sensor (barely visible to the human eye)
- Object recognition (human & vehicle): Video content analysis with fully automatic differentiation between people/vehicles and disturbances (branches, light, etc.)
- Intelligent video analysis with automatic detection of scenes (smart events) for precise motion alarms, recording and process optimisation; output of 3 video streams in ideal resolution for e.g. live image, recording, mobile access, etc.
- Robust, weatherproof housing (IP67), colour: black
- Supports H.264, H.265, MJPEG (incl. Dynamic GOP)
- microSD card slot for internal data storage, encrypted for high data security (optional)
- 12 V DC & PoE (802.3af)

Technical data - IP Mini Tube 4 MPx Black (2.8mm, WL)

Alarm generation	E-Mail, App Push, FTP, CMS
Aperture at minimum illumination (color)	F1.0
Application purpose	General surveillance
Article program	Professional
Audio	Integrated: Microphone
Backlight compensation	WDR, BLC, HLC
Camera type	Mini Tube
Colour	black
Compatible with ABUS Link Station	Yes
Compatible with Secoris	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes

IP Mini Tube 4 MPx Black (2.8mm, WL)

Art.-Nr. IPCS34611A

Seite 3 von 4

Technical data - IP Mini Tube 4 MPx Black (2.8mm, WL)

Connections	1 x RJ45, 1 x DC
Construction type of device	Mini tube
Current consumption	600 mA
DC power supply	12 (+/-25 %) V
Depth	223 mm
Digital zoom	Yes
Dimensions	(LxWxH) 223x85x85 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/100000 s
Encryption	HTTPS, TLS 1.1/1.2
Focal length	2,8 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps
Gross weight	0.7 kg
Height	85 mm
Horizontal viewing angle	108 °
Housing material	Metal
IR LEDs	No
Image integration	Yes
Image optimization	WDR, BLC, HLC, 3D DNR, Vertical Display (not in Smart-Event mode)
Image sensor	1/1.8" Progressive Scan CMOS
Language Manual	DE, UK, FR, NL, DK
Language OSD	DE, UK, FR, NL, DK, IT
Length	223 mm
Lens	Fix
Max. Air humidity	95 %
Max. Operating temperature	60 °C
Max. Resolution @ frame rate	2688 x 1520 @ 30 fps
Microphone	Yes
Min. operating temperature	-25 °C
Minimum illumination (color)	0.0005 lx
Motion detection	8 zones
Net weight	0.5 kg
Network bandwidth Video	32 kBit/s - 8 MBit/s
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ABUS Server, P2P, QoS, 802.1X, IGMP, Bonjour, PPPoE, SNMP
Network connection LAN	RJ45 10M/100M self-adaptive
Noise suppression	3D DNR
Number of streams	3
Number of users	32

IP Mini Tube 4 MPx Black (2.8mm, WL)

Art.-Nr. IPCS34611A

Seite 4 von 4

Technical data - IP Mini Tube 4 MPx Black (2.8mm, WL)

Other functions	Object Classification Person/Vehicle
PSTI conformity given	Yes
PSTI conformity needed	Yes
Pixels (effective)	2688(H) x 1520(V)
PoE Standard	IEEE 802.3af
Power consumption	7 W
Privacy zones	4
Product group	Camera
Protection class IP	67
Radio functions	Scene Change Detection, Region of Interest
Radio networked	No
Resolution	4 MP
Resolution modes	Stream 1: 2688 x 1520 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1920 x 1080 @ 10 fps (only in surveillance mode)
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	MS Edge, IE11, Mozilla Firefox, Google Chrome
Vertical angle of view	55 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection, Region Entrance, Region Exit
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265 (only in surveillance mode)
Video motion detector included	Yes
WEEE group	09
White balance	AWB, Manual
White light LEDs	2 St.
White light range (up to)	30 m
width	85 mm