

EasyLook pan/tilt camera

Art.-Nr. PPDF17620X

Seite 1 von 2

Technical data - EasyLook pan/tilt camera

Areas of application	Outdoor use
Article program	Comfort
Base event	Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000; PPDF17100
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Controllable with app	No
DC power supply	12 V
Day/night switching	Auto
Dimensions	210 x 120 x 160 mm
Encryption	WPA2
Focal length	4,1 mm
Frequency range	2,403 - 2,478 GHz
Horizontal viewing angle	85 °
Housing material	Plastic
IR LEDs	Yes
IR range (up to)	15 m
Image sensor	1/3" CMOS
Location	Outdoor use
Loudspeaker	Yes
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Max. Resolution @ frame rate	2304 x 1296 @15fps
Microphone	Yes
Min. humidity	30
Min. operating temperature	-10 °C
Minimum illumination (IR)	0.1 lx
Minimum illumination (color)	1 lx
Net weight	0.41 kg
Optical wavelength	940
Pan/tilt range	270° / 90°
Plug type	DC-plug: 5,5 x 2,0 mm
Power consumption	3.75 W
Power supply	Power adapter

EasyLook pan/tilt camera

Art.-Nr. PPDF17620X

Seite 2 von 2

Technical data - EasyLook pan/tilt camera

Privacy zones	4
Product group	Video sets
Protection class IP	66
Radio functions	People recognition, Night vision, Zoom, Intercom (2-way audio)
Radio range	(Depending on installation) 20 - 50 m
Resolution modes	2304 x 1296 (3MP)
Sensitivity	-88 dBm
Transmission power	20 dBm
Vertical angle of view	45 °
Video bitrate	2Mbps
Video compression	H.264+
Video system	Stand-alone
WEEE group	09
White balance	Auto