

Smartvest Pro wireless water detector

Art.-Nr. FUWM45000

Seite 1 von 2



Monitoring for protection against water damage in the cellar and other locations

When this discreet tool comes into contact with water from a faulty device or broken pipe, it reports it immediately. The Smartvest Pro control panel then sounds a high-volume alarm and all connected users receive a push notification through the Smartvest Pro app.

The sensitive records in the cellar, the valuable systems in the technology room or all the floors and furnishings in the kitchen and living area: aren't we all always a bit nervous when we think of unexpected water damage occurring in these rooms? The Smartvest Pro wireless water detector provides a solution. As soon as the compact detector comes into contact with water, all connected users receive a push notification through the Smartvest Pro app. The Smartvest Pro control panel also immediately issues a high-volume alarm.

Whether it's from a leak in the washing machine, dishwasher or water tank, an overflowing shower or bathtub or a broken water pipe, the Smartvest Pro wireless water detector is there to keep watch around the clock. Even when you've disarmed the Smartvest Pro security system's intruder alarm while you're home. The detector's battery is long-lasting and easy to replace. For a comfortably secure home. For you and your family.

Technologies

- Placed in the kitchen, technical room, cellar etc., Smartvest Pro wireless water detectors reliably detect and report accumulations of water
- For protection against water damage
- Triggers the alarm and starts all the custom scenarios configured in combination with the Smartvest Pro wireless alarm system
- Simply place on the surface you want it to monitor
- Includes easily replaceable battery

Smartvest Pro wireless water detector

Art.-Nr. FUWM45000

Seite 2 von 2

Technical data - Smartvest Pro wireless water detector

Areas of application	Interior
Battery - battery operation	Yes
Battery - max. battery life	2 years(s)
Battery - permanently installed	No
Battery - quantity	1
Battery type	CR2032 (3V)
Colour	white
Current consumption standby	0.01 mA
Diameter	65 mm
Dimensions	Ø 65 x 25 mm
Gross weight	0.077 kg
Height	25 mm
Housing material	Plastic
Max. Air humidity	90 %
Max. Operating temperature	40 °C
Min. humidity	10
Min. operating temperature	0 °C
Mounting type	Other
Net weight	0.046 kg
Product group	Detectors
Radio frequency	868.3 MHz
Radio modulation	FSK
Radio range	Depending on installation max. 100 m
Transmission power	11,3 dBm
WEEE group	09